



TORO.

TIMU



Count on it.

Designed for Homeowners

Toro has a wide portfolio of ride on mower options for any size garden, large or small. The Toro range has many patented technologies and features, designed to make our mowers noticeably more comfortable and easy to use, whilst delivering the excellent standards of finish you expect from a quality mower.

Toro ride on mowers are engineered to efficiently handle extreme conditions and challenging terrain, without sacrificing cut quality or your comfort. Their unmatched maneuverability for cutting around trees and landscaping, power and durability, all contribute to produce long-lasting performance.

Which one is right for you?

Whether it's for dependable performance, maneuverability or heavy-duty applications, Toro has a mower that's right for you.

Lawn Tractor XLS

BEST FOR:

Durable and dependable performance and ease of use operation.



TimeCutter[®] Series

BEST FOR: Maneuverability and time saving.

Titan[®] MX Series

BEST FOR:

Heavy-duty applications where terrain is more rugged.



TORO. Count on it.

Lawn Tractor XLS

The Ultimate in Power and Performance

KEY FEATURES



KeyChoice™

Toro's KeyChoice[™] reverse operation system improves safety during operation in reverse without diminishing performance.



Floating Deck Floating centrally mounted steel cutting deck offers superb contour following.



Tight Turn Radius A tight 50.8 cm turning radius allows close trimming around trees or other obstacles in the yard.

Toro XLS Lawn Tractors are side discharge tractors that combine power, performance and value. Combining modern styling and precision engineering, the robust XLS tractor series is designed to appeal to customers with large lawns to maintain. The automatic transmission is intuitive to use and transitions seamlessly between forward and reverse. The solid construction, including a cast-iron front axle, will provide dependable service for years.

Model No	XLS 380 (71254)	XLS 420T (71255)
Engine	452 cc Toro [®] OHV Single Cylinder	603 cc Kawasaki® V-Twin FR541V
Cutting Width	38" (96.5 cm)	42" (106.7 cm)
Deck Material	Steel	Steel
Ground Speed	0 - 8.6 km/h - forward, 0 - 1.5 km/h - reverse	0 - 8.6 km/h - forward, 0 - 1.5 km/h - reverse

IDEAL FOR 1 ACRE





Toro[®] Premium OHV Engine

Built to maximum performance. The overhead valve (OHV) design makes it more efficient and burns cleaner than side-valve engines. Special governor design delivers fast power when put under load (on model 71254).









Washout Port Easily clean grass and debris from under the deck. Attach a garden hose and turn on the water supply.



Robust Design Stress-resistant channel steel frame, tough durable cast-iron front axle provides durability for years to come.









TimeCutter® Series **Make the Smart Choice**

are an even smarter choice.

Smart Speed[™] Control System

Toro's exclusive Smart Speed[™] control system takes the time-saving speed and agility of a zero-turn mower and adds greater control. This exclusive Toro innovation lets you choose different ground speed ranges with the flip of a lever without changing the blade or engine speeds. You can mow large, open areas with the high speed range to finish quickly, or easily flip to the low speed range for controlled maneuvering around trees, gardens and landscaping.





For more than 25 years, Toro has been manufacturing cut along with the time savings of zero-turn technology.

Zero-Turn	lechnology
and Save 1	ſime

zero-turn mowers that deliver an outstanding quality of Just as Toro is the choice of professional landscapers, Toro TimeCutter[®] mowers are the smart choice for you. You'll mow like a pro and you'll do it all in a lot less time.

Model No	74621	74616	74389	74386	74390	74387	74395
Engine	452 cc Toro® OHV	452 cc Toro [®] OHV	597 cc Kohler® SV600	603 cc Kawasaki® V-Twin FR600V	726 cc Kawasaki® V-Twin FR691V	726 cc Kawasaki® V-Twin FR691V	726 cc Kawasaki® V-Twin FR691V
Cutting Width	32" (81.3 cm)	42" (106.7 cm)	42" (106.7 cm)	42" (106.7 cm)	42" (106.7 cm)	50" (127 cm)	50" (127 cm)
Deck Material	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Fabricated Deck	Stamped Steel	Fabricated Deck
Ground Speed	0 - 11.3 km/h	0 - 11.3 km/h	0 - 11.3 km/h	0 - 11.3 km/h	0 - 11.3 km/h	0 - 11.3 km/h	0 - 11.3 km/h
	IDEAL FOR	IDEAL FOR	IDEAL FOR	IDEAL FOR	IDEAL FOR	IDEAL FOR	IDEAL FOR

With the TimeCutter[®] series you can now spend more time enjoying your lawn and less time

mowing it. A lot less time. The Toro TimeCutter[®] is so maneuverable, it can cut your mowing

time in half. And with the addition of the Smart Speed[™] control system, TimeCutter[®] mowers



Work Smarter, Not Harder

The time saved with a Toro zero-turn mower quickly adds up. Find your yard size on this graph and discover how much mowing time our customers have reported saving with their Toro zero-turn mower.



4 ACRES

*See your dealer for full details on warranties.

4 ACRES











TimeCutter[®] Series Continued

KEY FEATURES



Automatic Parking Brake Automatically engages when the control arms are moved outward. Eliminates the need for a separate parking brake, making operation easy.



Powerful Engines Powerful Toro[®], Kohler[®] and Kawasaki[®] engines provide smooth, quiet and optimal power.





Comfortable Seats 15" (38.1 cm) mid back or 18" (45.7 cm) high back seats provide ample back support for a smooth, comfortable ride.



TORO

Deep 10.2 cm Steel Deck and 10.8 cm Fabricated Deck Provides superior cutting performance in all conditions.



11.4 Litre Fuel Tank with Sight Gauge

Higher capacity fuel tank lets you mow longer and the convenient sight gauge provides a quick view of the fuel level. The large petrol cap makes filling up easy.



42" (106.7 cm) and 50" (127 cm) Toro TimeCutter[®] ZS Mowers with Fabricated Decks -Rugged and Reliable

From the dual hydrostatic drive system and the heavy-duty 10 gauge fabricated cutting deck with bull-nose bumper to the powerful Kawasaki[®] twin-cylinder engines, Toro TimeCutter[®] ZS mowers with fabricated decks are built tough for dependable and long-lasting performance.





Dual Hydrostatic Drive System Provides independent power to each wheel for maximum traction and maneuverability.



Heavy-duty 10 Gauge Frame Provides increased strength, durability and reliability.



Toro Recycling System

The Toro Recycler mulching system creates your own natural fertilizer. This patented system cuts grass clippings 6-8 times turning them into a fine nutrient-rich mulch to feed your lawn all season. The secret lies in the unique 'kickers' and baffles that direct clippings back into the blades to be re-cut before being released into your lawn.

TORO. Count on it.





Titan[®] MX Series Ready for the Toughest Demands

The TITAN® MX combines pro-inspired features from our popular commercial line with the user-friendly features of our residential zero-turn mowers to create a commercial-like machine that's easy to use and comfortable to operate. The TITAN® MX gives you pro-like performance with Kawasaki engines, large wide tyres and heavy-duty decks and frame for taking on the toughest challenges. And if your neighbours think you hired a professional, well, just smile and show them your rugged, powerful TITAN® MX.

TORO.

Model No	74871	74872	74873
Engine	726 cc Kawasaki® V-Twin 21.5 hp	726 cc Kawasaki® V-Twin 23 hp	726 cc Kawasaki® V-Twin 24 hp
Cutting Width	48" (121.9 cm)	54" (137.2 cm)	60" (152.4 cm)
Deck Material	Fabricated Deck	Fabricated Deck	Fabricated Deck
Ground Speed	0 - 12.1 km/h	0 - 12.1 km/h	0 - 12.1 km/h
	IDEAL FOR 4 ACRES		IDEAL FOR 5 ACRES

KEY FEATURES

Pro-Inspired

The TITAN® MX leverages professional features similar to those found on our commercial zero-turn mowers to change your experience of mowing forever. Each component adds to the strength and durability of the machine, providing long-lasting, superior performance.



Smooth Front Tyres and Large Rear Tyres

30.5 cm x 15.2 cm smooth front tyres reduce turf wear and improve maneuverability. The 56 cm x 25.4 cm large, wide rear tyres provide a smoother ride over rough terrain than smaller diameter tyres.



Fully-Tubular Frame

3.8 cm x 7.6 cm fully-tubular frame offers superior strength and durability.

User-Friendly Residential Expertise

Our zero-turn mowers are all about saving time, ease-of-use and low maintenance. These user-friendly and comfort-focused features are built into every TITAN[®] MX, making it the best mower for the biggest yards.



Effortless Maintenance Quick, no-tools deck removal allows easy access to deck for maintenance.



LIFETIME

LIMITED WARRANTY

HOUR

LIMITED WARRANT

YEAR

Foot-Operated Height-of-Cut Quickly raise or lower the deck while keeping hands on the controls.

*See your dealer for full details on warranties.



Heavy-Duty Deck Spindles

Huge 19.7 cm diameter aluminium spindle housings contain 2.5 cm diameter spindle shafts.



Roll Over Protection System (ROPS)

Folding Roll Over Protection System (ROPS) comes standard. The folding design folds easily with the help of quick-release pins. It tucks under the frame for compact storage or when mowing under low obstacles on flat ground.



Fabricated Decks Up to 152.4 cm Wide

Fabricated, fully-welded decks with bull-nose bumpers handle tough cutting conditions and deliver a superior quality of cut.



Premium Seat with 3-D Isolation Toro premium seat with 3-D isolation mounts to absorb vibration.



Removable Floor Pan Allows easy access to the top of the deck for cleaning off grass clippings.



Commercial Grade Transmissions Heavy-duty ZT3100 transmissions are used with charge pumps, shock valves and heavy-duty gears.







Customise Your Mower with Genuine Toro Attachments and Accessories

ATTACHMENTS AND ACCESSORIES



Tow-Behind Dump Cart Transporting material is easy with this heavy-duty poly bed large dump cart.



Recycler[®] Mulch Kit Optional recycler kit cuts and re-cuts clippings into fine particles and redirects them back into the turf for a healthy looking lawn.



Twin Bagger Attaches easily and is great for cleaning up grass clippings

and leaves.

Product Cover

resistant cover.

Protect your investment with

a water, abrasion and tear



Bimini Folding Sunshade

Optional fabric shade for 2-post ROPS shields the operator from the elements.



Anti-Vibration Floor Mat This newly designed rubber floor mat is a great addition to your TimeCutter[®]/Titan[®] MX mower. Reduce vibration and dampens deck noise during mowing.



Hour Meter Keep your mower in peak condition by adding an hourmeter for determining service maintenance.

Foot Assist Height of Cut System

Allows you to quickly and easily raise the mowing deck while mowing to avoid scalping and can also be used to lift the mowing deck while changing height of cut positions.



Heavy-Duty Rear Engine Guard

This heavy-duty steel guard protects the engine from branches and debris as you nimbly maneuver around your lawn (for TimeCutter SS models).

Bumper Guard Kit

The cast iron front bumper guard kit provides extended life and durability (available for Lawn Tractor XLS models only).



Light Kit

Gives you the option to mow your grass in low light conditions.



Armrest Kit Adjustable armrests improve operator productivity by

Warranty

Building the best machines in the industry allows us to back them with the best warranty in the industry. Ask your dealer to learn about our warranty coverage.

- 2 year Limited Warranty on Lawn Tractor XLS mowers
- 3 year Limited Warranty on TimeCutter[®] ZS and SS mowers
- 3 year or 400 hours[^] Limited Warranty on Titan[®] MX mowers and a limited lifetime frame warranty

'Whichever occurs first.

"Original owner only. Lifetime Frame Warranty — If the main frame, consisting of the parts welded together to form the tractor structure that other components such as the engine are secured to, cracks or breaks in normal use, it will be repaired or replaced under warranty at no cost for parts and labor. Frame failure due to misuse or abuse and failure or repair required due to rust or corrosion are not covered.





YEAR

Finance

Purchasing Toro products is easy and affordable with special Toro sponsored finance promotions available through your participating certified Toro independent dealer.







The hitch kit is easily attached, which allows you to increase the functionality of your mower by allowing you to pull light duty attachments.

E-Z VAC Powered Bagger

Provides extra vacuum power to bag even wet grass and leaves. The blower reduces clogging and maximises bag filling.

(fits Titan & Titan MX model years 2010 & newer)

Cargo Carrier

Perfect for light duty hauling capabilities for mulch, soil, garden tools and other items for working in the yard. No "jack knifing" and it's easy to store.

(fits TimeCutter model years 2011 & newer. Fits Titan model years 2009 & newer.)



SPECIFICATIONS

	Lawii Ira	ctor XLS		TimeCutt	er® Series	
	XLS 380	XLS 420T	TimeCutter® SS 3200	TimeCutter® SS 4216	TimeCutter [®] ZS 4200S CE	TimeCutter® ZS 4200T CE
Model No	71254	71255	74621	74616	74389	74386
Power System						
	452 cc	603 cc	452 cc	452 cc	597 cc	603 cc
Engine**	Toro [®] OHV Single	Kawasaki® V-Twin	Toro® OHV Single	Toro® OHV Single	Kohler® Single Cylinder	Kawasaki® V-Twin
	Cylinder	FR541V	Cylinder	Cylinder	SV600	FR600V
Engine Guard	-	-	Optional	Optional	Standard	Standard
Starter	Electronic	Keystart		Electronic	c Keystart	
Drive System	Automa	ic Drive		Dual Hydrostatic Hy	/dro-Gear® ZT 2100	
Fuel Capacity	6.61	itres		11.4	litres	
Ground Speed (Maximum F/R)	8.6 / 1.	5 km/h		Smart Speed™ 11.3 / 5	Control System .6 km/h	
Tyres (Rear)	45.7 cm x 24.1 cm – 20	.3 cm, Turf Saver, 4 ply	45.7 cm x 15.2 cm	45.7 cm x 19 cm	45.7 cm x 19 cm	45.7 cm x 19 cm
Tyres (Front)	38.1 cm x 15.2 cm – 15	.2 cm, Turf Saver, 4 ply			ooth (2013 model) bed (2014 model)	1
Digital Hour Meter	-			Opti	ional	
Mowing Decks				· · · · · · · · · · · · · · · · · · ·		
Cutting Width	38"	42"	32"	42"	42"	42"
	(96.5 cm)	(106.7 cm)	(81.3 cm)	(106.7 cm)	(106.7 cm)	(106.7 cm)
Deck Material	Ste	el	Stamped steel – Single blade	Stamped steel – Twin blade	Stamped steel – Twin blade	Stamped steel – Twin blade
Deck Depth	10.2	cm		10.2	? cm	
Deck Mount	Deck suspended from front fr and attached to lift mechan		Deck suspe	ended from front frame by to lift mechanism by	y a single trunnion rod a two hanger brackets	nd attached
Deck Spindles	17.0 mm dia. Spindle shaft, die cast aluminium spindle housing (2) with permanently lubricated precision ball bearings		19.9 mm dia. spindle shaft, die cast aluminum spindle housing (1) with permanently lubricated precision ball bearings	17.0 mm dia. spindle shaft, die cast aluminum spindle housing (2) with permanently lubricated precision ball bearings		
Discharge Deflector	Moulde	d plastic		Moulde	d plastic	
Height of Cut	3-10.2 cm in	6 increments		3.8-11.4 cm ir	7 increments	
Blade Tip Speed ^{††}			18,959 ft/min @3400 rpm	17,810 ft/min @3400 rpm	15,150 ft/min @2900 rpm	15,150 ft/min @2900 rpm
Anti-Scalp Rollers	Standard	Standard	-	-	Standard	Standard
Foot Assist HOC	-	-		Opti	ional	1
Frame Gauge	13-gauge form	ed steel frame			auge	
5	Opti		Ontional	Optional	Standard	Standard
Recycler Kit			Optional			Standard
Washout Port	Stan	dard		Stan	dard	
User-Friendly Featu				1		
Seat	28 cm Deluxe flip up seat	33 cm Deluxe flip up seat	38.1 cm Mid back	38.1 cm Mid back	38.1 cm Mid back	45.7 cm High bac
Steering Levers/Control	35 cm s	oft lock	Dual wrap	o-around levers control th	e hydraulic pumps in the	e transaxles
Turning Radius	50.8	cm		Zero radius	s turn (ZTR)	
Adjustable Armrests	-			-	Optional	Optional
Folding ROPS	-	-	-	-	-	-
Removable Floor Pan				-	-	-
Dimensions Overall Length	180.3 cm	180.3 cm	182.4 cm	182.4 cm	182.4 cm	182.4 cm
Overall Width	118.1 cm	134.6 cm	99.4 cm	136.7 cm	136.7 cm	136.7 cm
	(deck included)	(deck included)	(deflector down)	(deflector down)	(deflector down)	(deflector down)
Overall Height	101.6 cm	101.6 cm	94.7 cm	94.7 cm	105.4 cm	105.4 cm
Weight	230 kg	240 kg	200.9 kg	228.2 kg	229.1 kg	230 kg
Warranty*	2 ye	ars		3 ye	ears	

*See dealer for full warranty details. **The gross or net torque of this engine was laboratory rated by the engine manufacturer in accordance with the appropriate SAE specification. As configured to meet safety, emission and operating requirements, the actual engine torque on this class of mower will be significantly lower. We reserve the right to improve our products and make changes in the specifications, designs and standard equipment without notice and without incurring obligation.

	TimeCutter [®] Series		
TimeCutter® ZS 4200TF	TimeCutter® ZS 5000 CE	TimeCutter® ZS 5000TF	
74390	74387	74395	
Power System			
726 cc Kawasaki®	726 cc Kawasaki®	726 cc Kawasaki®	
V-Twin	V-Twin	V-Twin	
FR691V	FR691V	FR691V	
	Standard		
	Electronic Keystart		
Dual Hydrostatic Hydro-Gear [®] ZT 2100	Dual Hydrostatic Hydro-Gear [®] ZT 2200	Dual Hydrostatic Hydro-Gear [®] ZT 2800	ļ
	11.4 litres		
	Smart Speed [™] Control System 11.3 / 5.6 km/h		ļ
45.7 cm x 19 cm	45.7 cm x 24 cm	50.8 cm x 25.4 cm	1
	33 cm x 12.7 cm Ribbed		
	Standard		
Mowing Decks			
42" (106.7 cm)	50" (127 cm)	50" (127 cm)	
Fabricated deck	Stamped steel	Fabricated deck	
10.8 cm	10.2 cm	10.8 cm	
	m front frame by a single trunni t mechanism by two hanger bra		ľ
	ndle shaft, die cast aluminum sp nanently lubricated precision ba		
	nanently lubricated precision ba		
	nanently lubricated precision ba Moulded plastic		
with perr 17,810 ft/min	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min	II bearings 18,330 ft/min	
with perr 17,810 ft/min	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm	II bearings 18,330 ft/min	
with perr 17,810 ft/min	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard	II bearings 18,330 ft/min	
with perr 17,810 ft/min	Moulded plastic Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard	II bearings 18,330 ft/min	
with perr 17,810 ft/min	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge	II bearings 18,330 ft/min	
with perr 17,810 ft/min	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard 10-gauge Standard Standard Standard Standard	II bearings 18,330 ft/min	
with perr 17,810 ft/min @3400 rpm	Moulded plastic Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard Standard	II bearings 18,330 ft/min	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back	Moulded plastic Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard Standard	II bearings 18,330 ft/min @3400 rpm	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard 10-gauge Standard Standard 5tandard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard	II bearings 18,330 ft/min @3400 rpm	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back	Moulded plastic Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard	II bearings 18,330 ft/min @3400 rpm	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard 10-gauge Standard Standard 5tandard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard	II bearings 18,330 ft/min @3400 rpm High back	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back	Moulded plastic Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard	II bearings 18,330 ft/min @3400 rpm High back	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back	Moulded plastic Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard Standard	II bearings 18,330 ft/min @3400 rpm High back	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back Dual wrap-around 182.4 cm 182.4 cm 137.2 cm	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard 45.7 cm I levers control the hydraulic pur Zero radius turn (ZTR) Padded armrests standard - 182.4 cm 160 cm	Il bearings	
vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back Dual wrap-around 182.4 cm	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard 45.7 cm I levers control the hydraulic pur Zero radius turn (ZTR) Padded armrests standard - 182.4 cm	Il bearings	
Vith perr 17,810 ft/min @3400 rpm Jser-Friendly Features 45.7 cm High back Dual wrap-around 182.4 cm 137.2 cm (deflector down)	Moulded plastic 3.8-11.4 cm 7 positions 16,650 ft/min @3100 rpm Standard Standard 10-gauge Standard Standard Standard 45.7 cm H levers control the hydraulic pur Zero radius turn (ZTR) Padded armrests standard - - 182.4 cm 160 cm (deflector down)	Il bearings	

 $^{\dagger\dagger}\textsc{Blade}$ tip speed is the theoretical maximum speed in feet per minute and is likely to vary.





TORO Count on it.

Your local certified Toro dealer:

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs, and standard equipment without notice and without incurring obligation. The gross horsepower of the engines have been laboratory rated by the various engine manufacturers. As configured to meet safety, emission and operating requirements, the actual engine horsepower on this class may be significantly lower.

Many of the products you will find in certified Toro dealers' stores come with a warranty or guarantee from The Toro Company. In addition, our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Full details of your consumer rights may be found at www.consumerlaw.gov.au

*See your certified Toro dealers for details on all of our warranties.

TORO070214/IND-C0123 02-2014

Toro Customer Service 1800 356 372 toro.com.au