

DO MORE... WITH MORE.

The Workman® MD Series with SRQ™ combines a coil-over shock absorber suspension design with an Active In-Frame™ twister joint. These features deliver superior ride quality for optimum operator comfort and control. The upgraded suspension and steering make the new Workman MDX and MDX-D easier and more comfortable to operate and control. Improved braking performance and the double-walled polyethylene tray for better uv protection are some of the features in the new Workman MDX and MDX-D. The new rack and pinion steering reduce steering effort by over 60%, while also tightening the feel. The hefty payload capacity and four-wheel hydraulic brakes combine with SRQ to provide enhanced productivity to tackle the toughest jobs. The Workman MDX & MDX-D have the power and versatility to help you do more, with more!



toro.com/mdx

F E A T U R E S

• More Power

A 480 cc petrol engine powers the Workman MDX and a 600 cc diesel engine powers the MDX-D to an impressive 1,250 lbs. (567 kg) cargo capacity and 1,200 lbs. (544 kg) towing capacity. This vehicle is built to haul your toughest load to any jobsite and features hydraulic brakes on all four wheels to safely stop you when you get there.

• More Comfort

The SRQ™ suspension boasts an independent A-frame front suspension with coil over shock absorbers that cushion bumps in the terrain, regardless of your payload. It works together with the proprietary Active In-Frame™ twister joint that allows each axle to follow ground

contours independently. The result is a smooth ride that you and your team will notice immediately. Operators experience less fatigue and stay more productive throughout the day.

• More Control

An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and move throughout the property more safely.

• More Durable

Virtually unbreakable exterior components make the Workman MDX and MDX-D more durable and dependable. This vehicle is built to work as hard as you do, year after year.

• More Accessories

A deluxe hard cab, canopy top and windshield provide protection from the sun or the elements. The roll-over protective structure (ROPS), brush guard, and optional all-terrain tyres help you operate in more challenging terrain. Add the deluxe or portable refreshment centre to turn your Workman into a revenue producing machine.

• Improved All Season Cab

The new improved ROPS-certified cab has tighter manufacturing tolerances and the bottom half of the doors are now metal which prevents incidental shattering of doors when opening into curbs. The fully enclosed deluxe hard cab closure includes seat belt and a sliding window or solid window on the Operator's side.

	WORKMAN MDX MODEL 07235TC	WORKMAN MDX-D MODEL 07236TC	
ENGINE	480 cc, 16 hp (11.93 kW) air-cooled, two-cylinder, Briggs & Stratton® Vanguard®. Meets EPA & CARB exhaust & evaporative emissions regulations.	600 cc, 16.8 hp (12.5 kW) liquid-cooled, 2-cylinder, Kubota® diesel. Biodiesel ready for use up to B-20 (20% biodiesel and 80% petroleum blend).	
SRQ™ SYSTEM	Active In-Frame™ twister pivot joint, front and rear suspension.		
FRONT SUSPENSION	Independent "A"- Frame with coil over shock absorbers.		
REAR SUSPENSION	Trailing arm with coil over shock absorbers.		
GROUND SPEED	16 mph (25.7 km/h) governed. Optional 20 mph (32 km/h) requires ROPS and seatbelts.		
BRAKES	Front wheel hydraulic disc. Rear wheel hydraulic drum.		
FRAME	Welded steel channel and tube in body construction. Frame surfaces are dipped e-coat. Body and bed constructed of dent and corrosion-resistant polyethylene.		
GROUND CLEARANCE	Front: 10" (25.4 cm), Rear: 7" (18 cm)		
TYRES	Front: 22 x 9.5-10, 4-ply, Rear: 24 x 12-10, 4-ply. Optional all-terrain tyres.		
FUEL CAPACITY	6.5 gallons (24.6 litres)		
DIMENSIONS	Width 59" (150 cm)	Length 117.75" (299 cm)	Wheel Base 81" (205.7 cm)
TURNING CLEARANCE CIRCLE	Inside rear tyre: 87" (221 cm), outside front tyre: 257" (653 cm).		
INSTRUMENTATION	Hour meter, low oil pressure warning light, accessory power port. Dash has 2 cup holders, radio holder and glove box storage.	Hour meter, oil pressure, glow plug, coolant temperature, battery charge indicator lights and accessory power port. Dash has 2 cup holders, radio holder and glove box storage.	
STARTING	Pedal start (optional key start)	Key start	
CARGO BED SIZE	Length: 44.5" (113 cm), Width: 49" (124.5 cm), Height: 10.25" (26 cm), LLDPE resin.		
TOTAL VEHICLE PAYLOAD CAPACITY	1,650 lbs. (750 kg)		
CARGO BED PAYLOAD CAPACITY	1,250 lbs. (567 kg)		
TRAILER TOWING CAPACITY	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 1,200 lbs. (545 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.		
OPTIONAL ACCESSORIES	Canopy, Solid or Folding Windshield, Electric Bed Lift, HD Bumper, Brush Guard, ROPS, Brake/Tail/Signal Light Kit, Deluxe Hard Cab, Portable Refreshment Centre, Heater Kit, HD Trailer Hitch and optional all-terrain tyres.		
WARRANTY	Two-year or 1500 hour limited warranty. Refer to the Operator's Manual for further details.		

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

The Workman MDX/MDX-D are manufactured in Tomah, WI ISO 9002 Certified Plant.



toro.com.au

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258



facebook.com/toroaus
twitter.com/toroaus
youtube.com/toroaustralia

