# **NETWORK LTC™ PRO SATELLITES**



# Upgrade from LTC™ Plus to LTC™ Pro

Why LTC Pro? Toro LTC Pro upgrade kits and satellites are designed to provide an upgrade path to Lynx. Once a system has been upgraded to LTC Pro completely, the firmware can be upgraded and the system can move from SitePro to Lynx. The intuitive user interface simplifies faceplate functions for ease of use and increased programmability in a single controller. The LTC Pro Satellite provides modular flexibility, fewer electrical connectors and superior surge protection for added reliability in lightening prone areas.

# **FEATURES** & BENEFITS

#### **Intuitive User Interface**

Simplifies faceplate functions.

## **Enhanced Manual Operations**

- · Runtimes to the second
- Stackable multi-manuals
- Start/Pause/Stop

## **Backwards Compatible with SitePro**

It will keep working with your existing SitePro Central until you are ready to move to Lynx.

#### **Enhanced Diagnostics**

Link monitor, System monitor, sequence station and station test.

# **Modularity Provides Flexibility**

Available from 16 to 64 stations in 8 station increments to meet your needs.





LTC™ Pro Upgrade Kit



# **SPECIFICATIONS**

## **Dimensions**

• 43.2 cm (W) x 40.6 cm (D) x 101.6 cm (H)

# **Operation Specifications**

- 16 to 64 stations in 8 station increments
- Field programmable for future upgrades
- Does not require EPROM(s) replacement
- Operates as a stand-alone controller or under the management of a central computer
- Supports wireline or radio communications with the central computer
- Supports hybrid communication (wireline and radio) for increased flexibility and cost effectiveness
- 16 irrigation programs
- Independent stand-alone and central operation
- Multi-Manual, Program Start and Syringe manual operations
- Operates up to 6 stations simultaneously

# **Electrical Specifications**

Input Power

• 230 to 240 VAC, 50 Hz: 0.21 amps (no load) 115-120 VAC

0.91 amps (maximum load) 115-120 VAC

Output Power

• 24 VAC: 3.0 amps (max. total load)

Temperature

Operating Temperature: -10°C to 60°C
Storage Temperature: -30°C to 65°C

#### **ORDERING INFORMATION**

Model	Description
118-4838	LTC Plus to LTC Pro Upgrade Kit
LTCR16P6M4	16-Station Green Plastic Pedestal, Electric, Wireline with Terminal Block, Switches and Gold Level Surge Protection
LTCR16P6R4	16-Station Green Plastic Pedestal, Electric, Radio with Terminal Block, Switches and Gold Level Surge Protection
LTCR40P6M4	40-Station Green Plastic Pedestal, Electric, Wireline with Terminal Block, Switches and Gold Level Surge Protection
LTCR40P6R4	40-Station Green Plastic Pedestal, Electric, Radio with Terminal Block, Switches and Gold Level Surge Protection
102-0654	8-Station Output Module
102-0642	M4 Surge, PCB Upgrade Kit

