Print Date: 30/03/2017



Toro Hypr-Oil 500

Toro Australia

Chemwatch Hazard Alert Code: 2

Print Date: 30/03/2017

Safety Data Sheet according to WHS and ADG requirements

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier	
Product name	Toro Hypr-Oil 500
Synonyms	Not Available
Other means of identification	Not Available
Relevant identified uses of th	e substance or mixture and uses advised against
Relevant identified uses	Automotive Lubricant.
Details of the supplier of the	safety data sheet
Registered company name	Toro Australia
Address	53 Howards Road, Beverly, South Australia 5009, Australia
Telephone	08 8300 3633
Fax	08 8243 2940
Website	www.toro.com.au
Email	info.au.toro.com
Emergency telephone number	er e e e e e e e e e e e e e e e e e e
Association / Organisation	State EPA
Emergency telephone numbers	000 (Police, Fire, Ambulance)
Other emergency telephone numbers	Poisons Information 131 126

SECTION 2 HAZARDS IDENTIFICATION

SIGNAL WORD

WARNING

Classification of the substan	
Poisons Schedule	Not Applicable
[1] Classification	Reproductive Toxicity Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Label elements	
GHS label elements	

Chemwatch: **5198-38** Page **2** of **11** Issue Date: **23/12/2015**

Toro Hypr-Oil 500

Version No: **3.1.1.1** Print Date: **30/03/2017**

Hazard statement(s)				
H361	Suspected of damaging fertility or the unborn child.			
Precautionary statement(s) P	Prevention			
P201	Obtain special instructions before use.			
P281	Use personal protective equipment as required.			
Precautionary statement(s) R	Response			
P308+P313	IF exposed or concerned: Get medical advice/attention.			
Precautionary statement(s) S	storage			
P405	Store locked up.			
Precautionary statement(s) D	Precautionary statement(s) Disposal			
P501	Dispose of contents/container in accordance with local regulations.			

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
Not Available	5-10	proprietary engine oil additive	
64742-65-0.	1-5	paraffinic distillate, heavy, solvent-dewaxed (severe)	
64742-55-8.	1-5	paraffinic distillate, light, hydrotreated (severe)	
64742-54-7.	1-5	paraffinic distillate, heavy, hydrotreated (severe)	
Not Available	1-5	automotive gear oil additive, mixture	
Not Available	1-5	severely treated base oil	
113706-15-3	1-5	zinc O,O-bis(sec-butyl & isooctyl)dithiophosphate	

SECTION 4 FIRST AID MEASURES

Eye Contact	If this product comes in contact with the eyes: ► Wash out immediately with fresh running water. ► Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ► Seek medical attention without delay; if pain persists or recurs seek medical attention. ► Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ► Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ► Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Print Date: 30/03/2017

Toro Hypr-Oil 500

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Version No: 3.1.1.1

- Foam.
 Dry chemical powder.
 BCF (where regulations permit).
- Carbon dioxide.
 Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
vice for firefighters	
Fire Fighting	 ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. ▶ Avoid spraying water onto liquid pools. ▶ DO NOT approach containers suspected to be hot.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. Fon combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include:
	, carbon dioxide (CO2) , sulfur oxides (SOx) , other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.
HAZCHEM	Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Moderate hazard. ► Clear area of personnel and move upwind. ► Alert Fire Brigade and tell them location and nature of hazard. ► Wear breathing apparatus plus protective gloves. ► Prevent, by any means available, spillage from entering drains or water course.	Minor Spills	 ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb spill with sand, earth, inert material or vermiculite. ▶ Wipe up.
► No smoking, naked lights or ignition sources. Personal Protective Equipment advice is contained in Section 8 of the SDS.		 ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ No smoking, naked lights or ignition sources.

Print Date: 30/03/2017

Toro Hypr-Oil 500

SECTION 7 HANDLING AND STORAGE

Version No: **3.1.1.1**

Precautions for safe handling	g	
Safe handling	 ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. 	
Other information	 ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. 	
Conditions for safe storage,	including any incompatibilities	
Suitable container	 ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks. 	
Storage incompatibility	▶ Avoid reaction with oxidising agents	

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	paraffinic distillate, heavy, solvent-dewaxed (severe)	Oil mist, refined mineral	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	paraffinic distillate, light, hydrotreated (severe)	Oil mist, refined mineral	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, refined mineral	5 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name		TEEL-1	TEEL-2	TEEL-3	
paraffinic distillate, heavy, solvent-dewaxed (severe)	Pump oil; (petroleum distillates, solvent de-waxed heavy paraffinic		140 mg/m3	1,500 mg/m3	8,900 mg/m3	
Ingredient	Original IDLH	Revised	ed IDLH			
proprietary engine oil additive	Not Available	Not Available				
paraffinic distillate, heavy, solvent-dewaxed (severe)	NI-t A9-61-		Not Available			
paraffinic distillate, light, hydrotreated (severe)			Not Available			
paraffinic distillate, heavy, hydrotreated (severe)			Not Available			
automotive gear oil additive, mixture	r oil additive, Not Available		Not Available			
severely treated base oil	e oil Not Available		Not Available			
zinc O,O-bis(sec-butyl & isooctyl)dithiophosphate Not Available		Not Available				

Chemwatch: 5198-38 Page 5 of 11 Issue Date: 23/12/2015

Toro Hypr-Oil 500

Exposure controls

Version No: 3.1.1.1

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Print Date: 30/03/2017

Personal protection







Eye and face

- Safety glasses with side shields.
- Ochemical goggles.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.

Skin protection

See Hand protection below

Hands/feet

▶ Wear chemical protective gloves, e.g. PVC.

▶ Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Body protection

See Other protection below

Other protection

- ▶ Overalls.▶ P.V.C. apron.
- Barrier cream.
- ▶ Skin cleansing cream
- ▶ Eye wash unit.

Thermal hazards

Respiratory protection

Not Available

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^{^ -} Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not

properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Clear amber liquid with characteristic odour, does not mix with water.

Physical state	Liquid	Relative density (Water = 1)	0.9

Toro Hypr-Oil 500

Version No: **3.1.1.1** Print Date: **30/03/2017**

Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	18.6 @ 100 deg C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	221	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological	effects
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

Chemwatch: **5198-38** Page **7** of **11** Issue Date: **23/12/2015**

Toro Hypr-Oil 500

Version No: **3.1.1.1** Print Date: **30/03/2017**

Based on experience with animal studies, exposure to the material may result in toxic effects to the development of the foetus, at levels which do

Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.

produce conjunctivitis.

establish effect on humans.

ZINC O,O-BIS(SEC-BUTYL &

ISOOCTYL)DITHIOPHOSPHATE

	not cause significant toxic effects to the mother. Substance accumulation, in the human body, may occur and may	cause some concern following repeated or long-term occupational exposure.
	TOXICITY	IRRITATION
Toro Hypr-Oil 500	Dermal (None) LD50: 2448 mg/kg	Not Available
	Inhalation (None) LC50: 9 mg/l	
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg	Not Available
	Inhalation (rat) LC50: >3.9 mg/l/4nr	
	Inhalation (rat) LC50: >4.7 mg/l/4nr	
paraffinic distillate, heavy,	Inhalation (rat) LC50: >5.2 mg/l/4nr	
solvent-dewaxed (severe)	Inhalation (rat) LC50: >5.3 mg/l/4nr	
	Inhalation (rat) LC50: 10.5 mg/l/4hr	
	Inhalation (rat) LC50: 5.7 mg/l/4nr	
	Inhalation (rat) LC50: 9.6 mg/l/4h	
	Oral (rat) LD50: >2000 mg/kg1	
	TOXICITY	IRRITATION
paraffinic distillate, light,	Dermal (rabbit) LD50: >2000 mg/kg	Not Available
hydrotreated (severe)	Inhalation (rat) LC50: 3.9 mg/L/4ft	
	Oral (rat) LD50: >2000 mg/kg1	
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg	Not Available
	Inhalation (rat) LC50: >3.9 mg/l/4h	
	Inhalation (rat) LC50: >4.7 mg/l/4hr	
	Inhalation (rat) LC50: >5 mg/l/4hr	
paraffinic distillate, heavy, hydrotreated (severe)	Inhalation (rat) LC50: >5.2 mg/l/4hr	
nyuron eateu (severe)	Inhalation (rat) LC50: >5.3 mg/l/4hr	
	Inhalation (rat) LC50: 10.5 mg/l/41	
	Inhalation (rat) LC50: 5.7 mg/l/4nr	
	Inhalation (rat) LC50: 9.6 mg/l/41	
	Oral (rat) LD50: >2000 mg/kg1	
zinc O,O-bis(sec-butyl &	TOXICITY	IRRITATION
isooctyl)dithiophosphate	Not Available	Not Available
Legend:	Value obtained from Europe ECHA Registered Substances - Acextracted from RTECS - Register of Toxic Effect of chemical Substances.	cute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data stances
PARAFFINIC DISTILLATI LIGHT, HYDROTREATE (SEVER	* Q8 MSDS	

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may

Dithiophosphate alkyl esters is corrosive and toxic to the tissues on skin or oral exposure depending on its concentration. Symptoms included

diarrhoea, skin and gastrointestinal irritation, lethargy, reduced food intake, staining about the nose and eye; occasionally, there was drooping of the eyelid, hair standing up, inco-ordination and salivation. Toxicity is reduced following inhalation (due to vapour pressure and high viscosity). It may produce reproductive, developmental and genetic toxicity on experimental animals, but no substantive data is available to

Toro Hypr-Oil 500

Print Date: 30/03/2017 Version No: 3.1.1.1

PARAFFINIC DISTILLATE. HEAVY. SOLVENT-DEWAXED

(SEVERE) & PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE. HEAVY, HYDROTREATED

(SEVERE)

The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives;

The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:

- The adverse effects of these materials are associated with undesirable components, and
- ${\scriptstyle \emptyset}$ The levels of the undesirable components are inversely related to the degree of processing;
- Distillate base oils receiving the same degree or extent of processing will have similar toxicities;
- The potential toxicity of residual base oils is independent of the degree of processing the oil receives.

The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.

Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential carcinogenic and mutagenic activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and

severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Mutagenicity and carcinogenicity testing of residual oils has been negative, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size.

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, **HYDROTREATED (SEVERE) &** PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)

For highly and severely refined distillate base oils:

In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative. The effects of repeated exposure vary by species; in animals, effects to the testes and lung have been

observed, as well as the formation of granulomas. In animals, these substances have not been found to cause reproductive toxicity or significant increases in birth defects.

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-**DEWAXED** (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, **HYDROTREATED (SEVERE) &** ZINC O,O-BIS(SEC-BUTYL & ISOOCTYL)DITHIOPHOSPHATE

No significant acute toxicological data identified in literature search.

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

(SEVER	<u> </u>		
Acute Toxicity	×	Carcinogenicity	
Skin Irritation/Corrosion		Reproductivity	~
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	

Legend:

- Data available but does not fill the criteria for
- classification
- Data available to make classification
- Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
paraffinic distillate, heavy, solvent-dewaxed (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, heavy, solvent-dewaxed (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, solvent-dewaxed (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, solvent-dewaxed (severe)	NOEC	504	Crustacea	>1mg/L	1
paraffinic distillate, light, hydrotreated (severe)	EC50	48	Crustacea	>1000mg/L	1

Issue Date: 23/12/2015 Chemwatch: 5198-38 Page 9 of 11

Toro Hypr-Oil 500

Version No: 3.1.1.1 Print Date: 30/03/2017

	1				
paraffinic distillate, light, hydrotreated (severe)	EC50	48	Crustacea	>10000mg/L	1
paraffinic distillate, light, hydrotreated (severe)	NOEC	504	Crustacea	>1mg/L	1
paraffinic distillate, heavy, hydrotreated (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, heavy, hydrotreated (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, hydrotreated (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, hydrotreated (severe)	NOEC	504	Crustacea	>1mg/L	1
	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite				

Legend:

V3 12

(QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Product / Packaging ▶ Where in doubt contact the responsible authority. disposal
 - ▶ Recycle wherever possible or consult manufacturer for recycling options. o
 - Consult State Land Waste Authority for disposal.
 - Bury or incinerate residue at an approved site.
 - ⁰ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labole Poquirod

 Labels Required	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Toro Hypr-Oil 500

Version No: **3.1.1.1** Print Date: **30/03/2017**

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE)(64742-65-0.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE)(64742-55-8.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)(64742-54-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

ZINC O,O-BIS(SEC-BUTYL & ISOOCTYL)DITHIOPHOSPHATE(113706-15-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status	
Australia - AICS	Y	
Canada - DSL	Y	
Canada - NDSL	N (paraffinic distillate, heavy, hydrotreated (severe); paraffinic distillate, heavy, solvent-dewaxed (severe); zinc O,O-bis(sec-butyl & isooctyl)dithiophosphate; paraffinic distillate, light, hydrotreated (severe))	
China - IECSC	Υ	
Europe - EINEC / ELINCS / NLP	N (zinc O,O-bis(sec-butyl & isooctyl)dithiophosphate)	
Japan - ENCS	N (paraffinic distillate, heavy, solvent-dewaxed (severe))	
Korea - KECI	Y	
New Zealand - NZIoC	Υ	
Philippines - PICCS	Y	
USA - TSCA	Y	
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

 ${\sf PC-TWA: Permissible \ Concentration-Time \ Weighted \ Average}$

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level Chemwatch: 5198-38 Issue Date: 23/12/2015 Page 11 of 11

Print Date: 30/03/2017

Toro Hypr-Oil 500

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Version No: **3.1.1.1**

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.TEL (+61 3) 9572 4700.end of SDS