

TORO

Z Master® 2000 Series

MEET YOUR NEW WORKHORSE.

Heads will definitely turn when you're towing one of the coolest bulls in our pen around town. But the Z Master 2000 really shines once it's off the trailer, as it's bulging at the seams with commercial performance, reliability and efficiency at an unbeatable value.

FINISH MORE JOBS FASTER THAN EVER with the powerful engines and upgraded hydros, and it's built to take on the toughest hits with a fully tubular frame, large 60.96 cm tyres and 7/10-gauge steel deck with bullnose bumper.

WORLD-CLASS COMFORT with hand-crafted seats and MyRIDE® Suspension System on selected models.

REST EASY knowing that Toro stands behind its mowers with a 4-year, 750-hour warranty.



Model shown 74490



NO MORE ROCKY RIDES

You shouldn't feel like you've gone 12 rounds with your lawn after mowing it. Save your body from the toughest terrain and avoid slow mowing speeds with the MyRIDE® Suspension System. *Select models.*



PRO DNA

Commercial DNA courses through these machines' veins with the same technology professionals depend on. Get a beautiful, professional-looking lawn.



LIGHT THE WAY

Built-in LED lights give you a superb panoramic view in dark conditions. *Select models.*



MADE TO LAST

Enjoy years of reliable performance with a fully tubular frame and 7/10-gauge steel deck.

QUICK CARRY SYSTEM

TRIPLE THREAT UTILITY KIT

Attach tools and accessories directly to the mower with innovative tool-mounting brackets. Includes Bucket Holder Kit, Universal Mount and Trimmer Mount. *Sold separately.*

4.6-6.1

Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



Z MASTER® 2000 SPECIFICATIONS*

	Z Master® 2000 48" 74490	Z Master® 2000 HDX 52" - MyRIDE® 74493	Z Master® 2000 HDX 60" - MyRIDE® 74494
POWER SYSTEM			
COMMERCIAL ENGINES AT 3600 RPM*	Toro 24.5 hp w/ HDAC	Toro 24.5 hp w/ HDAC	Toro 24.5 hp w/ HDAC
STARTER	Electric	Electric	Electric
HEAVY-DUTY DONALDSON® CANISTER-STYLE AIR CLEANER	Standard	Standard	Standard
DRIVE TYRES	61 x 24.1 – 30.5 cm	61 x 24.1 – 30.5 cm	61 x 24.1 – 30.5 cm
CASTER TYRES (CAGE BEARING)	33 x 16.5 – 15.2 cm	33 x 16.5 – 15.2 cm	33 x 16.5 – 15.2 cm
FUEL/CAPACITY	26.5 L	26.5 L	26.5 L
DIGITAL HOUR METER	Standard	Standard	Standard
LED LIGHTS	Optional	Standard	Standard
HYDRAULIC DRIVE SYSTEM	ZT-3400 Integrated Pumps & Wheel Motors	ZT-3800 Integrated Pumps & Wheel Motors	ZT-3800 Integrated Pumps & Wheel Motors
MAXIMUM FORWARD SPEED	16.1 km/h	17.7 km/h	17.7 km/h
CLUTCH	Electromagnetic	Electromagnetic	Electromagnetic
MOWING DECKS			
DECK SIZE	121.9 cm	132.1 cm	152.4 cm
CUTTING DECK	7/10-Gauge High-Strength Steel TURBO FORCE®	7/10-Gauge High-Strength Steel TURBO FORCE®	7/10-Gauge High-Strength Steel TURBO FORCE®
BULLNOSE BUMPER	Standard	Standard	Standard
RUBBER DISCHARGE CHUTE	Standard	Standard	Standard
DECK LIFT DESIGN	Extension Spring	Extension Spring	Extension Spring
SPINDLE HOUSINGS	20.3 cm Diameter Aluminum	20.3 cm Diameter Aluminum	20.3 cm Diameter Aluminum
2.5 CM (1") SPINDLE SHAFT	Standard	Standard	Standard
SPINDLE BEARINGS	Maintenance-Free	Maintenance-Free	Maintenance-Free
CUTTING HEIGHT	3.8 – 12.7 cm (.6 cm increments)	3.8 – 12.7 cm (.6 cm increments)	3.8 – 12.7 cm (.6 cm increments)
DECK DEPTH	12.7 cm	12.7 cm	12.7 cm
BLADES	0.5 cm Heat-Treated Steel	0.5 cm Heat-Treated Steel	0.5 cm Heat-Treated Steel
BLADE TIP SPEED	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min
BELT CONSTRUCTION	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt
FEATURES			
MyRIDE® SUSPENSION SYSTEM		MyRIDE® Suspension System	MyRIDE® Suspension System
COMFORT PLATFORM	-		
PLATFORM TRAVEL	-	7.62 cm	7.62 cm
SHOCKS	-	1 centre / 2 rear	1 centre / 2 rear
ADJUSTABILITY	-	5 Detents, Infinite Adjustability	5 Detents, Infinite Adjustability
OPERATOR SEAT	High-Back Suspension w/Armrests	Deluxe w/ Armrests	Deluxe w/ Armrests
STEERING CONTROLS	3.6 cm Diameter Grips; Adjustable, Dampened	3.6 cm Diameter Grips; Adjustable, Dampened	3.6 cm Diameter Grips; Adjustable, Dampened
FOLDING ROPS	Standard	Standard	Standard
TOOL-MOUNTING CAPABILITY	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready
LIFT MECHANISM	Quick-Attach Jack Ready	Quick-Attach Jack Ready	Quick-Attach Jack Ready
WARRANTY**	4 Year 750 Hour Limited	4 Year 750 Hour Limited	4 Year 750 Hour Limited
WEIGHTS & MEASUREMENTS			
WEIGHT	394.6 kg	459 kg	470 kg
ROPS HEIGHT (FOLDED)	124.5 cm	124.5 cm	124.5 cm
ROPS HEIGHT (UPRIGHT)	179.1 cm	179.1 cm	179.1 cm
DECK CLEARANCE WIDTH	134.6 cm	167.6 cm	134.6 cm
DEFLECTOR WIDTH	160.7 cm	191.1 cm	160.7 cm
LENGTH	208.3 cm	214 cm	208.3 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details. †CARB compliant model or model available.

We reserve the right to improve our products and make changes in the specifications, designs and standard equipment without notice and without incurring obligation.

toro.com.au

©2020 The Toro Company.
All Rights Reserved.
SEPT 2020



Count on it.