

Easy to Spot. Tough to Beat. Easy to install Pro-Loc tape fittings offer a comprehensive range of configurations including couplings, layflat take-offs and valve options. Engineered for use with quality 16mm and 22mm tape, Pro-Loc fittings are designed to last for the life of the irrigation system.

FEATURES & BENEFITS

Pro-Loc tape fittings deliver the quality you expect from Toro for reliable performance, season after season.

- Tight Seal Coarse thread ensures a tight seal, even in dirty conditions.
- Easy to Install Long double barb for positive installation.
- Easy to Grip Ergonomically designed nut provides a secure connection every time.
- Easy to See Bright blue nut makes tape fittings easy to find, remove and reuse.
- Low Profile Compact design doesn't interfere with retrieving the tape.
- UV Resistant Tough anti-UV stabiliser to suit Australian conditions.

Designed for reliable, proven results when used with Aqua-Traxx[™] PBX drip tape, Pro-Loc fittings are also suitable for use with other leading tape brands.





PRO-LOC™ TAPE FITTINGS

Couplings					
No. Constant	FTC500	16mm Tape Coupling			
	FTC700	22mm Tape Coupling			
	FTC800	25mm Tape Coupling			
Barb Takeoffs					
-	FTA5-250B	16mm Tape x Barbed Takeoff			
	1143-2300	(suit 101P4 Punch / 4.5mm hole)			
-	FTA5-400B	16mm Tape x Barbed Takeoff (suit 7.5mm hole)			
	FTA5-700B	16mm Tape x Barbed Takeoff (suit 13mm hole)			
	FTA7-700B	22mm Tape x Barbed Takeoff (suit 13mm hole)			
u	FTA5-425G	16mm Tape x Barbed Takeoff with Integral Gasket (requires 11.5mm hole)			
	FTA5-425GR	16mm Tape x Barbed Takeoff with Rubber Grommet*			
	FTA7-425GR	22mm Tape x Barbed Takeoff with Rubber Grommet*			
Threaded Adapto	rs	1			
	FTA5-75MPT	16mm Tape x 3/4" MBSP Adaptor			
	FTA7-75MPT	22mm Tape x 3/4" MBSP Male Adaptor			
	FTA5-75FHS	16mm Tape x 20mm Female Hose Swivel Adaptor			
Flush Valves					
7	FFVFPT-L	Automatic Flush Valve x 20mm Female Low Flow - White			
	FFVFPT-H	Automatic Flush Valve x 20mm Female High Flow - Red			
	FTA5-FVL	16mm Tape x Low Pressure Flush Valve			
	FTA7-FVL	22mm Tape x Low Pressure Flush Valve			
Layflat Takeoff Fi	ttings				
	FTA5-LF	16mm Tape x Layflat Takeoff - Single Grip**			
	FTA7-LF	22mm Tape x Layflat Takeoff - Single Grip**			
Barbed Adaptors					
	FTA5-500HB	16mm Tape x 16mm 0D tube Barbed Adaptor			
	FTA5-700HB	16mm Tape x 20mm 0D tube Barbed Adaptor			
	FTA7-700HB	22mm Tape x 20mm OD tube Barbed Adaptor			
Tees					
	FTT500	16mm Tape Tee			
	FTT700	22mm Tape Tee			

Barbed Tees				
	FTT5-500HB	16mm Tape x 16mm 0D tube Barbed Tee		
	FTT5-700HB	16mm Tape x 20mm 0D tube Barbed Tee		
Shutoff Valves				
	FTV500	16mm Tape Shutoff Valve		
	FTV700	22mm Tape Shutoff Valve		
Barbed Shutoff Valve with Locking Nut				
- 	FTV5-420BN	16mm Tape x Barb (suit 10mm hole) with Locking Nut Shutoff Valve		
	FTV7-500HN	22mm Tape x 16mm OD tube Barb with Locking Nut Shutoff Valve		
Barbed Shutoff Valves				
	FTV5-500HB	16mm Tape x 16mm OD tube Barbed Shutoff Valve		
	FTV7-500HB	22mm Tape x 16mm OD tube Barbed Shutoff Valve		
	FTV5-250B	16mm Tape x Barbed Shutoff Valve (suit 101P4 Punch / 4.5mm hole)		
	FTV5-400B	16mm Tape x Barbed Shutoff Valve (suit 7.5mm hole)		
Layflat Takeoff Shutoff Valves				
đ	FTV5-LF	16mm Tape x Layflat Takeoff Shutoff Valve - Single Grip **		
	FTV7-LF	22mm Tape x Layflat Takeoff Shutoff Valve - Single Grip **		
T-Handle Hex Tool				
├	LF-INST	T-Handle Hex Tool for Layflat Installation		
* 15mm or 0.59" drill size				

** requires a 16mm layflat punch *** 16mm or 0.63" drill size

Pro-Loc™ Fittings vs Tube Selection Guide				
Code	Tube Inner Diameter Tolerance (mm)	Wall Thickness Tolerance (mm)		
FTA5-500HB FTT5-500HB FTV500 FTV7-500HN FTV5-500HB FTV7-500HB	13.2 - 15.0	0.50 - 1.40		
FTA5-700B FTA7-700B FTA5-700HB FTA7-700HB FTT5-700HB FTT5-700HB FTV700	17.2 - 18.5	0.80 - 1.40		





PVC to Aquatraxx Offtake*







LD Poly to Aquatraxx Offtake

LD Poly to Aquatraxx Offtake



