



Introducing the bold new Toro Z Master® and GrandStand® Revolution Series commercial mowers.

Developed by Toro, industry-leading HyperCell® batteries deliver superior power that devours the lushest of lawns all day long...without bogging down! Built on the same proven GrandStand® and Z Master® chassis and TURBO FORCE® deck that you've trusted for years, the new Revolution Series delivers lower overall cost over the machine's lifetime.

PATENT-PENDING SOFTWARE CONTROLS

To optimise machine feel and response, including speed control

HYPERCELL® LITHIUM-ION BATTERY ALL-DAY RUNTIME

Toro designed to operate with machinery and meet landscaper needs

DECK RAKE ADJUSTMENT

To optimise runtime and quality of cut



toro.com.au

Customer Service 1800 356 372

©2023 The Toro Company. All Rights Reserved. IND-C0258 06-2023

"Warranty does not include battery. See your local Toro dealer or refer to owners manual for complete warranty details. "Whichever occurs first.

"Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation.

	GRANDSTAND®		Z MASTER® MyRIDE® SUSPENSION SYSTEM					
	18850	OTE	187	40TE	187	50TE	1876	S5TE
POWER SYSTEM	:						:	
Battery	HyperCell*		HyperCell*		HyperCell°		HyperCell*	
lattery Quantity	8		10		10		10	
attery Capacity	18.4 kWh		23.4 kWh		23.4 kWh		23.4 kWh	
untime (hrs)	4 - 7+		4 - 7+		4 - 7+		4 - 7+	
harge Time (hrs)	12		8		8		8	
harge Type	1.2 kW		3.3kW 240V Standard		3.3kW 240V Standard		3.3kW 240V Standard	
RACTION							:	
ransmission	Planetary Gearset		Planetary Gearset		Planetary Gearset		Planetar	y Gearset
lotors	Commercial High Torque		Commercial High Torque		Commercial High Torque		Commercial High Torque	
IOWING DECKS	:				:		:	
eck Size	52" (132.	.1 cm)	48" (1	21.9 cm)	▶ 52"	(132.1 cm)	▶ 60" (1	52.4 cm)
utting Deck	7-Gauge TURBO FORCE		7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®	
eck Discharge	Side		Side		Side		Side	
eck Depth	5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)	
	9" (22.9 cm) Diameter		9" (22.9 cm) Diameter		9" (22.9 cm) Diameter		9" (22.9 cm) Diameter	
pindle Housings	Cast Aluminum w/ Blade Retainer		Cast Aluminum w/ Blade Retainer		Cast Aluminum w/ Blade Retainer		Cast Aluminum w/ Blade Retainer	
utting Height	1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in 0.6 cm increments)		1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in 0.6 cm increments)		1.5" - 5.0" in .25" increments (3.8 - 12.7 cm in 0.6 cm increments)		1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in 0.6 cm increments)	
lades	.204" (0.5 cm) Heat-Treated Steel		.204" (0.5 cm) Heat-Treated Steel		.204" (0.5 cm) Heat-Treated Steel		.204" (0.5 cm) Heat-Treated Steel	
lade Tip Speed	Adjustable		Adjustable		Adjustable		Adjustable	
lectric Deck Lift	N/A		Optional		Optional		Optional	
otors	Mid-Mount Commercial High Torque		Mid-Mount Commercial High Torque		Mid-Mount Commercial High Torque		Mid-Mount Commercial High Torque	
ake Adjustment	Yes		Yes		Yes		Yes	
EATURES							:	
yRIDE* Suspension System	N/A		Standard		Standard		Standard	
perator Seat	N/A		Deluxe Comfort w/Armrests		Deluxe Comfort w/Armrests		Deluxe Comfort w/Armrests	
ax Traction Unit Speed	10 mph (16.1 km/h)		12 mph (19.3 km/h)		12 mph (19.3 km/h)		12 mph (19.3 km/h)	
ax Traction Speed Control	Yes - 7 speed settings		Yes - 7 speed settings		Yes - 7 speed settings		Yes - 7 speed settings	
rive Tyres	Super Turf 20" x 10" x 10"		Super Turf 24" x 9.5" x 12"		Super Turf 24" x 12" x 12"		Super Turf 24" x 12" x 12" (61 x 30.5 – 30.5 cm)	
rive Wheels	(50.8 x 25.4 – 25.4 cm) Black Steel		(61 x 24.1 – 30.5 cm) Black Steel		(61 x 30.5 – 30.5 cm) Black Steel		Black Steel	
TIVE WINEELS	Black Steel 11" x 4" - 5" Flat-Free		13" x 6.5" - 6" Flat-Free		13" x 6.5" - 6" Flat-Free		13" x 6.5" - 6" Flat-Free	
ront Caster Tyres	Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)	
echnology	Hour Meter, USB Included		Hour Meter, USB Included		Hour Meter, USB Included		Hour Meter, USB Included	
OPS Profile / PIN Type	N/A		Square Tube / Pin w/Lanyard		Square Tube / Pin w/Lanyard		Square Tube / Pin w/Lanyard	
nee Pad	Deluxe Durable		N/A		N/A		N/A	
perator Platform	Foldable w/Bumper Cushions		N/A		N/A		N/A	
ED Lights	Standard		Standard		Standard		Standard	
arking Brake	Integrated in Transmission Automatic		Integrated in Transmission Automatic		Integrated in Transmission Automatic		Integrated in Transmission Automatic	
ower Warranty*	5-Year/1200-Hour^ First 2-Year No Hour Limit		5-Year/1500-Hour^ First 2-Year No Hour Limit		5-Year/1500-Hour^ First 2-Year No Hour Limit		5-Year/1500-Hour^ First 2-Year No Hour Limit	
EIGHTS AND MEASUREME		-						
eight	1,109 lbs.	503.0 kg	1,354 lbs.	614.2 kg	1,381 lbs.	626.4 kg	1,461 lbs.	662.7 kg
DPS Height (Folded)	N/A	N/A	46.3"	117.6 cm	46.7"	118.6 cm	49.9"	126.7 cm
OPS Height (Upright)	N/A	N/A	71.6"	181.9 cm	72.1"	183.1 cm	72.1"	183.1 cm
eck Clearance Width	53.8"	136.7 cm	52.2"	132.6 cm	60.4"	153.4 cm	60.4"	153.4 cm
eflector Width	67.8"	172.2 cm	63.1"	160.3 cm	75.2"	191.0 cm	75.2"	191.0 cm
ength (Platform Up)	61.0"	154.9 cm	N/A	N/A	N/A	N/A	N/A	N/A
. J								