

The TORO logo is displayed in white, bold, sans-serif capital letters within a red rounded rectangular background.

Z MASTER[®] 7500-D SERIES



Looking for a workhorse mower that's easy to operate and gets the job done faster? Check out the Toro® Z Master® 7500-D. Highly productive 60" and 72" decks, and even a 96-inch deck design that folds up neatly for easy transport, then folds down to handle your biggest jobs — in half the time of comparable mowers.

The Toro® Z Master® 7500-D delivers all the speed and manoeuvrability of a zero turn, along with the superior quality of cut you expect from Toro.

SUPERIOR PERFORMANCE

Powered by Tier 4-compliant three-cylinder Yanmar® diesel engines, these mowers are packed with power to tackle the toughest mowing jobs.

EXTENDED SERVICE INTERVALS

Save on maintenance with extended service intervals and a deck design that uses matching blades. The mower is also backed by a 5-year/1,500-hour[^] warranty (first two years no-hour-limit). [^]Whichever occurs first.

MOW SMARTER

The 7500-D is equipped with Horizon™ Technology that lets you choose the right operating mode for the conditions, saving fuel costs while maintaining top-level performance.

Z MASTER® 7500-D	72028	72029	72074	72076	72098
POWER SYSTEM					
COMMERCIAL ENGINES AT 3600 RPM*	25 hp Yanmar® Diesel 1267cc	25 hp Yanmar® Diesel 1267cc	37 hp Yanmar Diesel 1642cc	37 hp Yanmar Diesel 1642cc	37 hp Yanmar Diesel 1642cc
HEAVY-DUTY CANISTER AIR CLEANER	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor
DRIVE TYRES	66.0 x 30.5 x 30.5 cm	66.0 x 30.5 x 30.5 cm	66.0 x 30.5 x 30.5 cm	66.0 x 30.5 x 30.5 cm	66.0 x 30.5 x 30.5 cm
CASTER TYRES	38.1 x 15.2 x 15.2 cm	38.1 x 15.2 x 15.2 cm	38.1 x 15.2 x 15.2 cm	38.1 x 15.2 x 15.2 cm	38.1 x 15.2 x 15.2 cm
FUEL/CAPACITY	Flat-Free Semi-Pneumatic	Flat-Free Semi-Pneumatic	Flat-Free Semi-Pneumatic	Flat-Free Semi-Pneumatic	Flat-Free Semi-Pneumatic
HOUR METER	47.3 litres	47.3 litres	47.3 litres	47.3 litres	47.3 litres
HYDRAULIC DRIVE SYSTEM	Horizon™ Technology	Horizon™ Technology	Horizon™ Technology	Horizon™ Technology	Horizon™ Technology
MAX GROUND SPEED (FWD)	17.84 cu cm Hydro-Gear HGM-H Motors with 18 cc Kanzaki® Pump	17.84 cu cm Hydro-Gear HGM-H Motors with 18 cc Kanzaki® Pump	17.84 cu cm Hydro-Gear HGM-H Motors with 18 cc Kanzaki® Pump	17.84 cu cm Hydro-Gear HGM-H Motors with 18 cc Kanzaki® Pump	17.84 cu cm Hydro-Gear HGM-H Motors with 18 cc Kanzaki® Pump
CLUTCH	20.1 km/h	20.1 km/h	20.1 km/h	20.1 km/h	20.1 km/h
MOWING DECKS	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc
DECK SIZE	60" (152.4 cm) (Rear Discharge)	72" (182.9 cm) (Rear Discharge)	72" (182.9 cm) (Rear Discharge)	72" (182.9 cm) (Side Discharge)	96" (243.8 cm) (Rear Discharge)
CUTTING DECK	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE®
BULL-NOSE BUMPER	Standard	Standard	Standard	Standard	Standard
DECK DEPTH	14.0 cm (5.5")	14.0 cm (5.5")	14.0 cm (5.5")	14.0 cm (5.5")	14.0 cm (5.5")
ADJUSTABLE DISCHARGE BAFFLE	N/A	N/A	N/A	Standard	N/A
RUBBER DISCHARGE CHUTE	N/A	N/A	N/A	Standard	N/A
DECK LIFT DESIGN	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch
SPINDLE HOUSINGS	22.9 cm (9") Diameter Cast Aluminium	22.9 cm (9") Diameter Cast Aluminium	22.9 cm (9") Diameter Cast Aluminium	22.9 cm (9") Diameter Cast Aluminium	22.9 cm (9") Diameter Cast Aluminium
2.5 CM (1") HEAVY-DUTY SPINDLE SHAFT	Standard	Standard	Standard	Standard	Standard
SPINDLE BEARINGS	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free
CUTTING HEIGHT	2.5 – 14.0 cm (1.0" – 5.5")	2.5 – 14.0 cm (1.0" – 5.5")	2.5 – 14.0 cm (1.0" – 5.5")	2.5 – 14.0 cm (1.0" – 5.5")	2.5 – 14.0 cm (1.0" – 5.5")
BLADES	3 blades at 52.1 cm (20.5") length	3 blades at 62.3 cm (24.5") length	3 blades at 62.3 cm (24.5") length	3 blades at 62.3 cm (24.5") length	4 blades at 62.3 cm (24.5") length
SHAFT DRIVE	Standard	Standard	Standard	Standard	Standard
ANTI-SCALP ROLLERS	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids	6 Standard	4 Standard, 2 Side Skids	13 Standard
FEATURES					
STEERING CONTROLS	4.1 cm Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	4.1 cm Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	4.1 cm Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	4.1 cm Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	4.1 cm Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)
OPERATOR SEAT	Standard	Standard	Standard	Standard	Standard
ARM RESTS	Standard	Standard	Standard	Standard	Standard
SEAT SUSPENSION SYSTEM	Standard	Standard	Standard	Standard	Standard
FOLDING ROPS	Standard	Standard	Standard	Standard	Standard
STORAGE COMPARTMENT	Standard	Standard	Standard	Standard	Standard
FLOOR PAN	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount
WEIGHTS AND MEASUREMENTS					
WEIGHT	887.7 kg	890.9 kg	972 kg	937.5 kg	1,202 kg
ROPS HEIGHT (FOLDED)	129.5 cm	129.5 cm	129.5 cm	129.5 cm	129.5 cm
ROPS HEIGHT (UPRIGHT)	182.4 cm	182.4 cm	182.4 cm	182.4 cm	182.4 cm
DECK CLEARANCE WIDTH	186.4 cm	198.9 cm	198.9 cm	186.4 cm	259.8 cm
LENGTH	245.1 cm	255.7 cm	255.7 cm	252.9 cm	247.3 cm



CONTOUR-FOLLOWING WING DECKS

Wing decks on the 96" model flex up 20 degrees and down 15 degrees to follow the terrain, hugging the ground for the smoothest possible cut. Folds to 72.5" to fit in trailer.



THE NEW STANDARD IN COMFORT

The floor pan and deluxe suspension seat are iso-mounted to reduce vibration. That results in a better operator experience and more productivity.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs, and standard equipment without notice and without incurring obligation. The gross horsepower of this engine have been laboratory rated by the engine manufacturer. As configured to meet safety, emission and operating requirements, the actual engine horsepower on this class may be significantly lower.

Many of the products you will find in certified Toro dealers' stores come with a warranty or guarantee from The Toro Company. In addition, our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Full details of your consumer rights may be found at www.consumerlaw.gov.au

*See your certified Toro dealers for details on all of our warranties.