

Made to move.

Built for work and designed for comfort, Toro Vista provides transportation across any property with ease.

Vista is available in 4-, 6- and 8-passenger models.

The polar white body and assortment of accessories allow for easy customisation no matter where the venue.

Toro Vista is the perfect choice for any campus, event space, resort and more. Impress your guests with quick and convenient transportation in the Toro Vista.



F E A T U R E S

• Power

Choose between Hypercell® lithium-ion battery or EFI Petrol engine to power your 4-, 6- or 8-passenger shuttle. Need more run time? Add an additional battery on your lithium models.

• Heavy-Duty Frames

The frame of each shuttle size is specifically designed to handle the anticipated weight. No need to worry about a bowed frame after years of use.

• Comfort

Comfort was top of mind when designing the shuttle with both the driver and passengers in mind. Experience ample storage, legroom, independent suspension and ergonomic design throughout.

• Parking Convenience

The electronically controlled parking brake seamlessly activates once the vehicle comes to a stop and deactivates when the driver presses the pedal (on Li models).

• Standard Equipment

LED headlights, rear/brake lights, fold-down rear seat, back-up alarm, horn, canopy and rearview mirror on 4-passenger models.

• Design

The sleek, professional design compliments the customer. Customers have the ability to paint, wrap or place decals on the TPO plastic body to customise their shuttle fleet.



	VISTA (ELECTRIC), MODELS 08924TC, 08926, 08928	VISTA (PETROL EFI), MODELS 08914TC, 08916, 08918
POWER SOURCE	Two Hypercell® lithium-ion batteries standard, option to add an additional battery	408 cc, air-cooled, single cylinder Briggs & Stratton® EFI petrol engine
CHARGER	On-board high efficiency 900 W smart charger AC input voltage 100-240 VAC AC input frequency 50/60 Hz Max input current 13.4 A	N/A
VALVE TRAIN	N/A	Single cylinder overhead valve
ELECTRIC MOTOR	Brushless high-torque AC induction motor with 5.0 kW continuous power	N/A
FUEL SYSTEM	N/A	Electronic fuel injection
HORSEPOWER (KW)	5 kW (6.7 hp continuous)	10 kW (14.0 hp)
KEY OR PEDAL START	Pedal start standard	Key and pedal standard
AIR CLEANER	N/A	HD air filter
LUBRICATION	N/A	Splash lube
COOLING SYSTEM	N/A	Air-cooled
FUEL CAPACITY	N/A	18.9 litres
FRAME	Welded steel with A-coat primer and powder coat	
BODY AND FINISH	Injection-moulded TPO	
OVERALL LENGTH	4-passenger: 277 cm (109") 6-passenger: 357 cm (140.5") 8-passenger: 437 cm (172")	
OVERALL WIDTH	112 cm (44")	
OVERALL HEIGHT (W/O ROOF)	To top of steering wheel: 121 cm (47.5")	
OVERALL HEIGHT (W/ ROOF)	To top of canopy: 188 cm (73.9")	
WEIGHT	4-passenger: 403 kg (890 lb) including the required canopy kit 6-passenger: 422 kg (930 lb) 8-passenger: 487 kg (1,075 lb)	4-passenger: 399 kg (880 lb) including the required canopy kit 6-passenger: 417 kg (920 lb) 8-passenger: 483 kg (1,065 lb)
WHEEL BASE	4-passenger: 166 cm (65.5") 6-passenger: 246 cm (97") 8-passenger: 326 cm (128.5")	
INSTRUMENTS/DASH	Display: Battery level indicator, estimated charge time, gear indicator, speedometer, diagnostics/fault codes. Dash: USB power port, headlight switch, on/off/neutral ignition key switch, forward/reverse switch, horn switch, indicator switch (optional), hazard switch (optional), beacon switch (optional), two cup-holders, storage compartments.	Display: Gear indicator, speedometer, diagnostics/fault codes. Dash: USB power port, headlight switch, on/off/start ignition key switch, forward/reverse lever, horn switch, indicator switch (optional), hazard switch (optional), beacon switch (optional), two cup-holders, storage compartments.
GROUND CLEARANCE	21.6 cm (8.5") at the front with no operator 15.7 cm (6.2") at the rear with no operator	
SEATING CAPACITY	4, 6 or 8-passenger options	
VEHICLE LOAD CAPACITY	4-passenger: 458 kg (1,010 lb) total 6-passenger: 689 kg (1,520 lb) total 8-passenger: 873 kg (1,925 lb) total All totals include 91 kg (200 lb) operator and 91 kg (200 lb) for each passenger, load, accessories and attachments.	4-passenger: 463 kg (1,020 lb) total 6-passenger: 694 kg (1,530 lb) total 8-passenger: 878 kg (1,935 lb) total All totals include 91 kg (200 lb) operator and 91 kg (200 lb) for each passenger, load, accessories and attachments.
SPEED	25.75 km/h (16 mph) standard, adjustable from 8-30.58 km/h (5-19 mph)	25.75 km/h (16 mph) standard, speed reduction kits available
STEERING	Rack and pinion	
SUSPENSION	4-wheel independent suspension with adjustable coil-over shocks	
SERVICE BRAKE	4-wheel hydraulic disc	
PARKING BRAKE	Automatic parking brake	Foot pedal with accelerator pedal release
TYRES (FRONT AND REAR)	205 x 65-10, 6 ply	
STANDARD	LED headlights, rear/brake lights, fold-down rear seat, back-up alarm, horn, canopy and rearview mirror on 4-passenger models.	
OPTIONAL ACCESSORIES	Canopy, folding windscreen, indicators, beacon, side mirrors, rear-view mirror, wide angle mirror, wink mirror, cargo bed (light duty).	
WARRANTY	Two-year or 1,500-hour warranty. Lithium-ion battery 5 years. Refer to the Operator's Manual for further detail.	

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

Vista vehicles are manufactured in Windom, MN ISO 9002 Certified Plant.



toro.com.au

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258



facebook.com/toroaus
twitter.com/toroaus
instagram.com/toroaus
au.linkedin.com/showcase/toroaustralia
youtube.com/toroaustralia

©2023 The Toro Company.
All Rights Reserved.
23-259-AU 11-2023

