LITHIUM-ION POWER.

Hypercell® lithium-ion technology that powers the Workman GTX Lithium is built to deliver hours of reliable performance. The GTX Lithium provides a large cargo capacity, so it can handle big jobs. At nearly 181.4 kg lighter than traditional Workman GTX models, it makes a big impression on productivity without leaving a big impression on turf. The lithium-ion power packs are maintenance-free and have a long lifespan, so the machine is always ready to get to work.



FEATURES

• Power

An improved power-to-weight ratio provides the capacity and productivity you need to do more, every day.

Cargo capacity

At 363.8 kg, the GTX Lithium-Ion provides a large cargo capacity.

• Maintenance-free

Lithium-ion battery packs require no maintenance, which allows you to spend less time checking batteries and more time ticking tasks off your to-do list.

• Extended battery life

Lithium-ion battery packs give you the power for long days and reduced charging time for short nights.

· Onboard charger

No need to keep track of your charger, it's onboard and ready to be connected to any standard power socket at any time, anywhere.

· Reduced weight

The GTX Lithium is 26% lighter than a traditional electric vehicle, and offers an additional 7.6 cm (3") of ground clearance, making it nimble while still packing plenty of all-day power.

• Choose your power

Option to add an additional battery for those looking for more power during the most demanding all-day jobs.

WORKMAN® GTX SERIES SPECIFICATIONS*

	WORKMAN GTX (LITHIUM-ION BATTERY) 07433TC
POWER SYSTEM	Lithium-ion batteries with integrated Battery Management System (BMS)
ENERGY CAPACITY	4.32 kWh standard, 6.48 kWh optional. 55 V nominal; 63 V max.
ELECTRIC MOTOR	Brushless high-torque AC induction motor with 5.0 kW continuous power.
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 35 cm (13.75") diameter.
TURNING RADIUS	Turning clearance circle: 6.3 m (20.7'), inside turning radius: 1.5 m (5').
BRAKES	Front and rear wheel hydraulic disc brakes.
SUSPENSION	Front: Modified MacPherson strut. Rear: Articulating swing arm. Adjustable coil-over shocks at all four wheels.
SUSPENSION TRAVEL	Front suspension travel: 89 mm (3.5") Rear suspension travel: 102 mm (4").
GROUND SPEED	25.6 km/h, adjustable.
TRANSAXLE	11.47:1 Forward, 14.35:1 Reverse.
GROUND CLEARANCE	Front: 30.4 cm (12"), Rear: 17.8 cm (7").
TYRES	22 x 9.5-12, 4-ply. Or alternate 4-ply/6-ply.
WHEELS	12" (30.5 cm) aluminium.
CONTROLLER	375 A max. with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes.
CHARGER	On-board high efficiency 900 W smart charger. •AC input voltage: 100–240 VAC •AC input frequency: 50/60 Hz •Max. AC input current: 10 A
INSTRUMENTS/DASH	Hour meter, battery-level indicator, USB power port, headlight switch, on/off ignition key switch and parking brake lever. Two cup holders, radio holder, three in-dash storage compartments, speedometer, gear indicator, estimated charge time and diagnostic/fault codes.
STARTING	Pedal start.
DIMENSIONS	Vehicle configurationWidthLengthHeight:Wheel base2-seat with bed (GTX lifted)119.3 cm (47")302 cm (119")135 cm (53.2")197 cm (77.8")
CAB DIMENSIONS INSTALLED	Height: 208 cm (82") Width: 142 cm (56")
CANOPY DIMENSIONS INSTALLED	Height: 199 cm (78.2") Width: 138 cm (54.3")
WEIGHT	Vehicle configuration: 2-seat with plastic cargo bed Weight: 445 kg
CARGO BED	Width: 97.8 cm (38.5") Length: 101.6 cm (40") Height: 27.9 cm (11") Capacity: 363 kg
VEHICLE CAPACITY	2-seat with bed 544 kg
TOWING CAPACITY	680 kg Class 1. 1.25" receiver standard.
OPTIONAL ACCESSORIES	Canopy, solid folding windscreen, storage box, rubbish bin mount, bed racking, electric bed lift, brush guard, 12 V outlet, brake/rear/indicator lights, ROPS-certified hard cab, back-up alarm kit, parking brake alarm kit, 2-post ROPS kit, range cage and glass windscreen.
WARRANTY	Two-year or 1,500-hour warranty. Refer to the Operator's Manual for further details. Battery warranty: 5-year, unlimited hours.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

The Workman GTX is manufactured in Windom, MN ISO 9002 Certified Plant.



toro.com.au

Customer Service 1800 356 372 ©2024 The Toro Company. All Rights Reserved. 23-208-GB 08-2024

See your local Toro distributor for details on all warranties.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, require attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation.

Many of the products you will find in certified Toro distributors' stores come with a warranty or guarantee from The Toro Company. In addition, our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Full details of your consumer rights may be found at www.consumerlaw.gova.













