



## WE 500

COMPACT UTILITY LOADER

Toro is introducing the next generation in electric compact utility loader: the Toro WE 500. Exceptional runtime in a compact design allows the WE 500 to fit in the tightest spaces and tackle the toughest of jobs. Ideal for indoor construction and demolition, the WE 500 is powered by the Hypercell® power system, a battery technology developed by Toro to match the power of traditional internal-combustion-powered products with zero engine-exhaust emissions and less noise. The WE 500 is optimised to deliver up to an eight-hour continuous runtime, while maintaining a 234 kg Rated Operated Capacity (ROC), allowing it to complete more jobs with less hassle.

### FEATURES



**76 cm width** – The new, next-generation WE 500 has a brand-new frame with a narrow footprint to easily fit through a 1-metre door

**Patented controls** – Operate the WE 500 with Toro's patented one-handed traction controls. This user-friendly design allows for smooth and precise movements at any skill level



**206 cm hinge pin height** – Industry-leading hinge pin height while maintaining 234 kg ROC

**Up to eight hours of continuous runtime\*** – The new WE 500 incorporates the Hypercell power system with over 13 kWh for up to eight hours of continuous runtime

*\*Runtime may vary based upon conditions and attachment being used.*

# WE 500

## SPECIFICATIONS



**76 cm width**



**Patented controls**



**206 cm hinge pin height  
Plus 234 kg ROC**



**On-board charger**

WE 500 (MODEL 22219)		
<b>BATTERY</b>	Capacity	13.57 kWh
	Chemistry	Lithium-Ion
	AC input voltage range	85–270 VAC
<b>HYDRAULIC SYSTEM</b>	Hydraulic pressure	22,408 kPa (3,250 psi)
	Hydraulic flow	24.6 lpm
	Reservoir capacity	27.28 l
<b>WHEELS</b>	Standard	Non-marking / Solid
<b>DIMENSIONS</b>	Wheelbase	71.12 cm
	Ground clearance	10.80 cm
	Overall dimensions (WxLxH) with bucket	106.25 cm x 223.52 cm x 137.80 cm
	Overall dimensions (WxLxH) without bucket	76.20 cm x 168.28 cm x 137.80 cm
	Maximum operating height	269.24 cm
	Hinge pin height	205.74 cm
	Dump height	154.94 cm
	Dump angle	38°
	Reach - Fully raised	54.61 cm
	Ground speed	4.43 km/h
	Weight	1,062.31 kg
	Tip capacity	567.44 kg
	Rated operating capacity	233.60 kg

### Attachments

Most existing Toro attachments are available, including:

- Buckets
- Floor scraper
- Adjustable forks
- Hydraulic breaker
- Grapple

### toro.com.au

Customer Service 1800 356 372  
©2024 The Toro Company. All Rights Reserved. 23-703-GB 08-2024

See your local Toro dealer for details on all warranties.

\*Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, require attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation.

Many of the products you will find in certified Toro dealers' stores come with a warranty or guarantee from The Toro Company. In addition, our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Full details of your consumer rights may be found at [www.consumerlaw.gov.au](http://www.consumerlaw.gov.au).

Follow @ToroAustralia on



**Count on it.**