

# **Plastic Spinner Sprinklers**

## **Application**

- For use in nurseries
- Low pressure 'butterfly' type sprinkler with rotating spinner, the economical alternative to the Rotoframe<sup>™</sup>.
- Manufactured from quality engineering plastics with stainless steel spindle.

### **Specifications**

- Inlet: 15 mm MBSP.
- Jet size: 3.1 mm.

kPa

100

150

200

250

- Flows: 4.4 Lpm to 7 Lpm.
- Diameters: 9.8 m to 11 m.

**Performance Chart** 

Lpm

4.4

5.5

6.4

7.0



An economical alternative.

Ordering Information		
Code	Description	
1015192	Butterfly Sprinkler	

TORO Ag Irrigation

# Rotoframe<sup>™</sup> Rotating Sprinklers

Dia (m)

9.8

11.0

10.8

10.5

### **Application**

- Nurseries
- Market Gardens

Lower pressure 'butterfly' sprinkler with rotating spinner and frame which provides improved water distribution.

 Die-cast zinc body, stainless steel spindle, plastic spinner and brass nut

Ordering Information		
Code	Description	
1015190	15 mm BSP Female	
1015191	20 mm BSP Female	

## **Specifications**

- Inlet: 15 mm FBSP and 20 mm FBSP.
- Jet size: 5 mm
- Flows: 11.8 Lpm to 16.2 Lpm.
- Diameters: 12.2 m to 13.4 m.

Performance Chart			
kPa	Lpm	Dia (m)	
100	11.8	10.9	
150	13.2	11.8	
200	14.7	12.0	
250	16.2	11.6	



Rotating spinner and frame provides improved water distribution.

Company policy is one of constant improvement and therefore changes in specifications may be made without notice and without incurring liability-Please refer to www.toro.com.au Toro Australia Pty Ltd, 53 Howards Road, Beverly, South Australia, 5009. Phone 1300 130 898, fax (08)8243 2488. A.B.N 47 001 310 443