



A turbulent flow, Pressure Compensating dripper available in 3 flows.

Applications

Pots, planter boxes, balcony, patio and landscape applications.

Features

- Take-apart for easy inspection and cleaning.
- Self-flushing action with insect baffle to minimise blockages.
- PC barbed dripper range: 2 lph, 4 lph and 8 lph with 4mm spout.
- Also available with 4mm barb outlets.
- Coloured bases to identify flow rates.
- 4 lph PC Spike and In-Line Spike models to anchor CETA® at the plant.

Performance	Discharge (lph)		
Pressure (kPa)	2 lph	4 lph	8 lph
50	1.9	3.3	6.2
100	2.0	3.8	7.9
150	2.2	4.2	7.9
200	2.3	4.4	8.1
250	2.3	4.4	8.1
300	2.3	4.4	8.0
350	2.2	4.3	7.8



Specifications					
Dimensions Assem	bled	CETA® PC	CETA® PC Spike/In-Line Spike		
Height Width Depth		25mm 20mm 16mm 1.7g	135mm 36mm/42mm 16mm 5.0g		
Weight (approx)					
UV Stabilised Material	Base/Spike Cap Diaphragm	polypropylene polypropylene silicone rubber	polypropylene polypropylene silicone rubber		
Connection Type: Ir Outlet	nlet	Barb 4mm Spout 4mm	Barb 4mm Spout 4mm		







CETA® PC					
Nominal Flow	Base Colour	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
2 lph	Red	10130425	100	70	13.3
4 lph	Black	10130445	100	70	13.3
8 lph	Green	10130485	100	70	13.3

CETA® PC 4 lph Spike				
Base Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Spike	10130625	25	40	6.3
In-Line Spike	10130655	25	40	6.3



CETA® PC 4 lph Spike 4mm

CETA® PC 4 lph In-Line Spike 4mm