

Application

Suitable for use in joining uPVC Pipe made to the Australian Standard AS 1477.

Features

- A wide range of uPVC fittings imported from the US
- The majority are schedule 40 fittings with the exception of some specialty fittings in schedule 80
- Schedule 40 fittings are white and not suitable for direct sunlight situations
- Schedule 80 fittings are grey and are UV stabilised
- Range of sizes from 15mm up to 250mm
- BSP and limited range of NPT threads

Range of fittings



Plain Tees



Faucet Tees



Reducing and Increasing Tees



Reducing Faucet Tees



Plain Elbows




Reducing Elbow, Slip x Slip




Spigot Elbows, Slip x Spigot



45° Elbows, Slip x Slip



Faucet Elbows
Slip x Female Thread




Reducing Faucet Elbows, Slip x
Female Thread



Street Elbows,
Slip x Male Thread



Side Outlet Elbows



Couplings, Slip x Slip



Reducing Coupling, Slip
x Slip




Valve Socket,
Slip x Male Thread



Reducing Valve Sockets, Slip
x Male Thread

Spears uPVC Fittings




Street Elbow, Male x Female



Side Outlet Elbow, Slip x Slip x Slip



Telescopic Repair Coupling, Slip x Slip



Compression Coupling



Barrel Union, Slip x Slip



Threaded Couplings



Swing Joints, Male BSP x Male BSP



Van Stone Flanges, Rotating Ring x Slip

Schedule 40/80 Pressure Rating

Nominal Pipe Dia. (mm)	Maximum Working Pressure (kPa)	
	Schedule 40	Schedule 80
15	4137	5860
20	3300	4757
25	3100	4343
32	2550	3585
40	2275	3240
50	1930	2758
80	1790	2550
100	1516	2206
150	1241	1930
195	1100	1723

Ordering Information

See Toro Australia Irrigation Division Price List