TORO Ag Irrigation

Aluminium Tubing

Toro Ag has a range of quality aluminium tubing to complement its fitting range. The tube is manufactured to a high standard with a robust seam for reinforcement.

Features

- Aluminium tube is supplied with plain ends
- Extruded irrigation tube produced to Australian Standard AS3795 – 1991
- Pressure tested to 2000 kPa
- Standard lenghth 9 m
- Non-standard lengths can be made subject to enquiry approval



Manufactured to a very high standard

| Nomimal Diameter (mm) | Mean Outside Diameter (mm) | Wall Thickness Diameter (mm) |
|--------------------------|-------------------------------|---------------------------------|
| 40 | 38.1 | 1.1 |
| 50 | 50.8 | 1.2 |
| 80 | 76.2 | 1.2 |
| 100 | 101.6 | 1.5 |
| 125 | 127 | 1.6 |
| 150 | 152.4 | 2.0 |

| Ordering Information | | | | |
|----------------------|----------------------------|----------------|-----------------|--|
| Code | Description | Tubes Per Pack | Min. Pack Order | |
| 1016321 | 40 mm \times 9 m Tubing | 60 | 2 | |
| 1016322 | 50 mm \times 9 m Tubing | 60 | 1 | |
| 1016323 | 80 mm × 9 m Tubing | 25 | 2 | |
| 1016324 | 100 mm \times 9 m Tubing | 14 | 2 | |
| 1016325 | 125 mm \times 9 m Tubing | 9 | 2 | |
| 1016326 | 150 mm \times 9 m Tubing | 6 | 3 | |

| Ordering Conditions | | | | |
|---------------------|--|--|--|--|
| 1. | Please note, standard mill packs will only be supplied. Orders must be complete multiples of mill pack. | | | |
| 2. | As this product is manufactured to order and is an extruded product, exact quantities cannot be guaranteed. Our supplier reserves the right to a shipping tolerance of \pm 20%. The order will be manufactured, shipped and considered complete. | | | |
| 3. | All orders are FOT to any metropolitan carrier of your choice. | | | |
| | confirm ordering requirements with Toro Australia Customer Service prior to quoting and nent of order. | | | |