



RW50-KIT

- Lilac identification kit, includes Lilac 588403 solenoid and non-potable warning swing tag.
- Fits EZ-Flo Plus, P-150, P-220 and 220 series valves
- Captive plunger
- 45cm Red leads, XLPE insulation, 20AWG conductors
- 24VAC, 50Hz, 0.34 amp inrush, 0.20 amp holding current



588403

- 811B Solenoid Assembly
- 24VAC, 50Hz, 0.34 amp inrush, 0.20 amp holding current
- 45cm Red leads, XLPE insulation, 20AWG conductors
- Captive plunger



DCLS-P

- Potted DC Latching solenoid suits EZ-Flo Plus, P-150, P-220 and 220 series valves. Suits DDCWP
- Wetted parts constructed from 400 stainless steel and zytel
- Voltage: 6-14VDC
- Coil resistance: 9 ohms
- Coil inductance: 65 mH
- Pulse width: 20ms
- Leads: 2, red and black, 45cm long, 20AWG, PVC insulation
- Latch position: + Red and - Black
- Unlatch position: + Black and - Red



DCL

- Potted DC Latching solenoid suits Richdel, 700 series and Century Plus series valves. Suits JRDC, RadioMaster, IBOC and IBOC Plus
- Wetted parts constructed from 400 stainless steel and zytel
- Voltage: 6-14VDC
- Coil resistance: 9 ohms
- Coil inductance: 65 mH
- Pulse width: 20ms
- Leads: 2, red and black, 45cm long, 20AWG, PVC insulation
- Latch position: + Red and - Black
- Unlatch position: + Black and - Red



HCV-KIT

- Converts standard solenoid operated valve into hydraulic remotely operated valve. Only suits Toro P150, P220, Irritrol Century, Century Plus and S-Series solenoid valves.
- Kit consists of a thread x 1/4" barbed adaptor (to replace the coil) and 2 PVC plugs. Suits Toro 1/4" control tubing.
- Cannot be used if EZReg or OmniReg required or fitted.