TORO Ag Irrigation

Mazzei[®] AirJection[®] Rainbow A-Series

Application

Used in conjunction with sub-surface ROOTGUARD® Drip Tube and Aqua-Traxx® tape systems to aerate the root zone and improve harvest results.

Rainbow A-Series injectors are designed to be installed one injector per lateral line.

- In areas with long above-ground submains.
- In areas with submains that have elevation changes.

Features

- Available in one 1/2 " and two 3/4" male NPT models.
- Motive flow rates ranging from 3.41 to 52.11 Lpm.
- 10%+ increase in yields as compared to conventional drip *
- 50% increase in root mass healthy and more vital plant *
- Less stress on plant as it is able to absorb water, air and soil nutrients simultaneously during the irrigation cycle.
- Ease of operation
- Efficient, compact venturi design with no moving parts
- Colour coded units for ease of identification
- Moulded from 40% glass filled polypropylene
- Increase in yields and root mass based on results obtained at a commercial farming operation and a study performed by CIT at CSU Fresno.





| Motive Flow - Litres per Minute | | | |
|---------------------------------|--------|---------|---------|
| Inlet Pressure kPa | MAI-A3 | MAI-A20 | MAI-A24 |
| 138 | 3.41 | 21.32 | 27.63 |
| 172 | 3.79 | 23.85 | 29.65 |
| 207 | 4.16 | 26.00 | 31.92 |
| 241 | 4.54 | 27.76 | 35.07 |
| 276 | 4.92 | 29.52 | 37.09 |
| 310 | 5.30 | 31.16 | 40.00 |
| 345 | 5.55 | 33.43 | 41.38 |
| 414 | 6.06 | 36.08 | 45.42 |
| 483 | 6.43 | 39.24 | 48.83 |
| 552 | 6.94 | 41.76 | 52.11 |
| Colour | Red | Tan | Brown |

Model A3 has 1/2" MNPT connections. Models A20 and A24 have 3/4" MNPT connections.

| Ordering Information | | |
|----------------------|--|--|
| Code | Description | |
| MAI-A3 | Mazzei Air Injector, 15mm MNPT, Red, 3.4-6.9 Lpm | |
| MAI-A20 | Mazzei Air Injector, 20mm MNPT, Tan, 21.3-41.7 Lpm | |
| MAI-A24 | Mazzei Air Injector, 20mm MNPT, Brown, 27.6-52.1 Lpm | |

Company policy is one of constant improvement and therefore changes in specifications may be made without notice and without incurring liability. Please refer to www.toro.com.au Toro Australia Pty Ltd, 53 Howards Road, Beverly, South Australia, 5009. Phone 1300 130 898, fax (08)8243 2488. A.B.N 47 001 310 443