

Irritrol Accessories



DCL Solenoid • Potted DC Latching solenoid suits Richdel, 700series and Century Plus series valves. Suits JRDC, RadioMaster, IBOC and IBOC Plus • Wetted parts constructed from 400 stainless Wetted parts constructed from 400 stamess steel and zytel Voltage: 6-14VDC Coil resistance: 9 ohms Coil inductance: 65 mH Pulse width: 20ms Leads: 2, red and black, 45cm long, 20AWG, DVC incutation

- **PVC** insulation
- Latch position: + Red and Black
 Unlatch position: + Black and Red



Parts for 204/205 MT





HCV-KIT

• Converts standard solenoid operated valve into hydraulic remotely operated valve. Only suits Toro P150, P220, Irritol Century, Century Plus and S-Series solenoid valves.

Kit consists of a thread x ¼" barbed adaptor (to replace the coil) and 2 PVC plugs. Suits Toro ¼" control tubing.
Cannot be used if EZReg or OmniReg required could be used if EZReg or OmniReg required

or fitted.



SPK-700-X


Prepackaged repair kit for UltraFlow® Series valves. Includes diaphragm assembly, support ring, seat seal, 0-rings and fasteners

SPK-700 — X	
Model	Size
SPK-70075	3/4"
SPK-700B75	3/4"
SPK-700-1	1″
SPK-700-1.5	1½″
SPK-700-2	2″



SPK-100-X

Prepackaged repair kit for Century Series valves. Includes diaphragm assembly, support ring, O-ring metering rod and fasteners





R100PX

Prepackaged repair kit for Century PLUS Series valves. Includes diaphragm assembly, support ring, 0-rings, metering rod and fastening nuts

R100P — X	
Model	Size
R100P1	1″
R100P1.5	1½″
R100P2	1″
R100P3	1″

Company policy is one of constant improvement and therefore changes in specifications may be made without notice and without incurring liability.Please refer to www.toro.com.au Toro Australia Pty Ltd, 53 Howards Road, Beverly, South Australia, 5009. Phone 1300 130 898, fax (08)8243 2488. A.B.N 47 001 310 443

245