

**In-Line Screen Filters**

- Three sizes available, 13 mm, 19 mm and 25 mm barbed.
- Maximum working pressure, 300 kPa.
- Single sealing cap to minimise leakages
- Replaceable nylon mesh element
- Mesh aperture approximately 0.4 mm x 0.25 mm



Plastic In-Line Filters

Ordering Information	
Code	Description
1011111	In-Line Filter 13 mm Barbed (40 mesh equiv.)
1011113	In-Line Filter 19 mm Barbed (40 mesh equiv.)
1011114	In-Line Filter 25 mm Barbed (40 mesh equiv.)
FFP1160	Replacement Cartridge (Suits 13, 19, 25mm)

**Clear-Flo™ PBS Plastic Body Screen Filter**

**Application**

- Ideal for the smaller drip and micro sprinkler systems with flows up to 6.0m<sup>3</sup>/hr.
- Hydraulic valve command water filtration
- Sizes available:  
 20 mm - Maximum Flow rate 1.8m<sup>3</sup>/hr (10 kPa loss)  
 25 mm - Maximum Flow rate 2.8m<sup>3</sup>/hr (10 kPa loss)  
 32 mm - Maximum Flow rate 4.5m<sup>3</sup>/hr (10 kPa loss)  
 40 mm - Maximum Flow rate 6.0m<sup>3</sup>/hr (10 kPa loss)

**Features**

- Male BSP connections
- Rugged corrosion resistant nylon canister and cap, stainless steel screen
- Easily dismantled for thorough cleaning
- Inox screen cartridge
- O'ring in Buna-N
- Locking ring glass reinforced Nylon 6
- Maximum working pressure: 1000kPa
- Available in 150 mesh / 100 micron



Ordering Information	
Code	Description
1011120	20 mm (3/4") - 150 Mesh Screen
1011122	25 mm (1") - 150 Mesh Screen
1011124	32 mm (1 1/4") - 150 Mesh Screen
1011126	40 mm (1 1/2") - 150 Mesh Screen
1011126SCN	150 Mesh Screen, to suit 1011120, 1011122, 1011124, 1011126