

GENUINE TORO COMPACT UTILITY LOADERS ATTACHMENTS



High-Speed Trencher

- Ideal for fast, efficient trenching in soft to medium soil conditions
- Heavy-duty nose roller bearing and reversible abrasion-resistant boom
- 60 cm, 91 cm and 112 cm booms available
- Auger speed: 187 rpm at 11gpm
- Torque: 600Nm at 3000 psi
- Weight: 177 kg.



High-Torque Trencher

- Guarantees performance in any soil condition from rock to clay
- Heavy-duty nose roller bearing and reversible abrasion-resistant boom
- 60 cm, 91 cm and 122 cm booms available
- Auger speed: 120 rpm at 11gpm
- Torque: 900Nm at 3000 psi
- Weight: 177 kg.



4 in 1 Buckets

Wide

- Heaped Capacity: 5.3 cubic feet
- Struck Capacity: 4.3 cubic feet
- Overall Width: 104 cm
- Overall Length: 58 cm
- Overall Height: 54.5 cm
- Overall Weight: 130 kg.

Narrow

- Heaped Capacity: 5.3 cubic feet
- Struck Capacity: 3.6 cubic feet
- Overall Width: 86 cm
- Overall Length: 58 cm
- Overall Height: 54 cm
- Overall Weight: 117 kg.

Leveller

- Grade, finish, and spread topsoil and other landscape materials
- Back fill trenches

- Carry job site materials such as plants, fertilizer, irrigation supplies, and more
- Length: 85 cm; Width: 124 cm; Height: 40 cm; Weight: 70 kg.



Vibratory Plow

- Optimizes pipe-pulling performance while minimizing turf damage to reduce time and labour spent on irrigation or cable installations
- Pulls pipe up to 46 cm deep
- Elliptical vibrating motion moves pipe through difficult soil conditions
- Head flexes side-to-side for tight turning

- Pipe size: up to 3.8 cm flexible polyethylene with standard bullet; 5.1 cm PVC or 36 kg polypipe with taperlock puller
- Swing angle: +/- 30°
- Plow cycle: 1390 vpm
- Max. plow speed: 27 m/min depending on soil conditions
- Overall length: 86 cm; Overall width: 72 cm; Overall height w/out blade: 69 cm; Overall weight: 203 kg.



Hydraulic Blade

- Designed for versatility, this 122 cm blade angles 30° both right and left with the flip of a lever
- The blade can be removed and rotated 180° to increase blade life
- Overall width: 122 cm; Overall height: 53 cm; Overall weight: 64 kg.

Power Box Rake

- Perfect tool for seed bed and sod bed preparation
- Easily adjust depth to fill, plane and pulverize soil
- Reversible end plates for forward or reverse operation
- Roller drum removes rocks and debris, leaving dimpled surface for moisture retention



- Adjustable yoke allows 20° offset
- Carbide-teeth rotary drum pulverizes rough soil, cuts high spots and fills low spots in one pass
- Overall width: 170 cm; Working width: 122 cm; Overall height: 102 cm; Overall length: 66 cm; Weight: 231 kg.

Soil Cultivator

- Prepares seed bed in one pass, tilling soil up to 14 cm deep
- Adjustable grading bar and comb teeth leave perfect germination environment
- Bury stones, soil clods, debris and grass



- Totally enclosed oil bath drive system increases power and torque to the tiller shaft and tines
- Working width: 91 cm
- Overall width: 130 cm; Overall height: 53 cm; Overall length: 130 cm; Weight: 195 kg.



Multi – Purpose Tool

- 3 tools in 1: ripper, towbar, boom
- Ripper: 3 thick steel tines — great for digging & breaking up soil
- Towbar: Accepts ball with 2.5 cm diameter threads (ball not included)
- Boom & chain length 114 cm; ideal for planting and hauling trees and shrubs.

GENUINE TORO COMPACT UTILITY LOADERS ATTACHMENTS



Tree Forks

- Opens wide to handle large trees and shrubs
- Angle design allows for gentle handling of materials
- Overall width: 62 cm; Overall length: 114 cm; Overall height: 32 cm; Opening at tip: 63 cm; Weight: 77 kg.



Buckets

- Standard bucket: Holds 4.3 cubic feet; Width: 107 cm
- Narrow bucket: Holds 3.5 cubic feet; Width: 88 cm
- Light materials bucket: Holds 6.9 cubic feet; Width: 122 cm
- Optional tooth bars available. See parts catalogue for details.

Stump Grinder

- Index position of blade adjusts up to 30°, allowing easy removal of roots
- Cuts up to 91 cm above and 53 cm below grade
- Wheel diameter: 34 cm; Teeth count: 12 carbide tipped; Wheel speed: 2000 rpm; Tooth tip speed: 45 m/sec
- Width: 112 cm with debris shield; Length: 51 cm; Height: 79 cm; Weight: 120 kg.

Bore Drive Head & Rod & Reamer Kit

- Easily bore under driveways and sidewalks to simplify irrigation and cable installations. Working depth: 49 cm
- Features universal joint keeping rods in horizontal digging position, regardless of head position
- Standard Rod & Reamer Kit: Boring Bit: 4.4 cm; Reamer: 6.3 cm; Drill rods (4): 2.2 cm diameter, by 1.5 m. Optional bits from 3.2 – 6.4 cm. Optional reamers up to 11.4 cm.



Tiller

- Heavy-duty, high-torque design
- Hardened steel tines for any soil condition, including clay or hardpan
- Till more than 15 cm deep and 102 cm wide on one pass
- Reversible tine direction frees jams quickly
- Tine speed: 226 rpm at 11 gpm
- Overall width: 112 cm; Overall length: 51 cm; Height: 66 cm; Weight: 165 kg.



Trench Filler

- Fill trenches in a single pass, saving time and money
- Two sets of opposing augers direct spoils into the hole
- Standard float mechanism allows for up to 12.7 cm of ground following floatation
- Skids evenly disperses weight and slide easily over turf, minimizing damage
- Overall width: 157 cm;
- Working width: 122 cm;
- Auger diameter: 35.6 cm;
- Float distance: 15 cm;
- Weight: 186 kg.



Hydraulic Breaker

- Horizontal and vertical positions for demolishing driveways, sidewalks, steps, or walls
- Powerful; delivers 244Nm of force and up to 1250 blows per minute
- Tool diameter: 4.5 cm; Overall width: 62 cm; Overall length: 127 cm; Weight: 119 kg
- Optional bits available: 5 cm chisel 16.5 cm asphalt; 20 cm tamper moil bit. See parts catalogue for details.



Universal Swivel Auger Power Head

- Ensures "plumb" holes on uneven terrain
- Recommended for augers up to 46 cm
- Perfect for installing fences
- Bit speed: 86 rpm at 11 gpm
- Torque: 1300Nm at 3000psi at 11 gpm
- Dig up to 2 metre holes
- Bit length 106 cm; 60 cm and 30 cm extensions available
- Optional cement bowl.

Backhoe

- Versatile — dig foundations, plant trees, trench and much more
- Folds to 86 cm wide for access to tight spaces and ease of transport
- 180° bucket and swing arm rotation, 208 cm digging depth, and standard 133 cm bucket
- Transport height: 180 cm
- Weight: 346 kg
- Stabilizer spread: 198 cm
- Bucket digging force: 1110 kg
- Crowd arm digging force: 566 kg.



Grapple Rake

- Exceptional power for clamping and holding
- Ideal for picking up and removing trees, bushes, roots and rocks — as well as demolition and construction debris
- Tines constructed of 9.5 mm AR400 steel*
- Overall width: 88 cm; Weight: 121 kg; Clamping force: 1359 kg.

*Nearly twice as hard, 50% better wear than T1 steel.



High-Torque Auger Power Head

- Designed specifically to power up to 76 cm diameter auger in tough soil conditions
- Excellent for digging holes for trees, footings or irrigation valve boxes
- 2054Nm at 3000 psi at 11 gpm
- Heavy-duty motor, casting and bearings
- Auger bits from 15 cm to 76 cm
- Bit length: 107 cm
- Bit speed: 57 rpm at 11 gpm
- 30 cm and 60 cm extensions available
- Optional cement bowl.



Adjustable Forks

- Easily adjust forks to desired width
- Carry fence posts, rocks, pallets, plants, fertilizer, irrigation supplies and more
- Forks constructed of high-strength T1 steel
- Lift capacity: 136 kgs; Maximum lift height: 155 cm; Width: 80 cm; Weight: 74 kg.

Cement Bowl

- Flighting mixes and holds cement in bowl
- Mix, haul, and pour up to 90.7 kg
- Auger power head required (sold separately)
- Diameter: 64 cm; Length: 46 cm; Weight: 34 kg.

