Mini 8 Performance Data					
Nozzle	Pressure	Flow	Radius	Prec. Rate	
	(kPa)	(Lpm)	(m)	△ □	
.75	200	3.0	6.1	5.6	4.8
	250	3.3	6.3	5.8	5.0
	300	3.8	6.5	6.2	5.4
	350	4.6	6.7	7.1	6.1
1.0	200	4.2	7.9	4.7	4.0
	250	4.6	8.1	4.8	4.2
	300	5.2	8.3	5.2	4.5
	350	5.7	8.6	5.3	4.6
1.5*	200	4.5	8.8	4.0	3.5
	250	5.0	9.0	4.3	3.7
	300	5.6	9.3	4.5	3.9
	350	6.1	9.5	4.7	4.0
2.0	200	5.3	9.1	4.4	3.8
	250	6.0	9.3	4.8	4.2
	300	6.8	9.4	5.3	4.6
	350	7.7	9.4	6.0	5.2
3.0	200	8.7	10.3	5.7	4.9
	250	9.4	10.6	5.8	5.0
	300	10.4	10.7	6.3	5.4
	350	11.5	10.7	6.9	6.0

<sup>\*</sup>Pre-installed nozzle. Radius shown in metres

 <sup>△</sup> Precipitation rates are for triangular spacing, shown in millimetres per hour, calculated at 50% of diameter.
□ Precipitation rates are for square spacing, shown in millimetres per hour, calculated at 50% of diameter.
All performance specifications are based on the stated working pressure available at the base of the sprinkler.

Lawn Pop-up Apex @ 280 kPa				
	25°			
Nozzle	Maximum Height of Spray			
0.75	0.95m			
1.0	1.55m			
1.5	2.04m			
2.0	2.32m			
3.0	2.32m			

 <sup>△</sup> Precipitation rates are for triangular spacing, shown in millmetres per hour, calculated at 50% of diameter.
□ Precipitaiton rates are for square spacing, shown in millmetres per hour, calculated at 50% of diameter.

See precipitation rate calculation in Technical Section.