

Specifications			
Valve Code	1014416	BFLV32	BFLV43
End Connections	2" x 2" Victaulic	3" x 3" Victaulic	4" x 4" Victaulic
Flush Connections	2" FBSP	2" FBSP	3" FBSP
Pressure Range	70-1600 kPa	70-1600 kPa	70-1600 kPa
Maximum Temperature	65° C	65° C	65° C
Valve Body	Brass	Polyester or epoxy coated Cast Iron	Polyester or epoxy coated Cast Iron
Separating Partition	Polyamide 6-30GF Black	n/a	n/a
Cover	Polyamide 6-30GF Black	Epoxy coated Cast Iron	Epoxy coated Cast Iron
Diaphragm	NR-AL52 Nylon Fabric reinforced	NR-AL52 Nylon Fabric reinforced	NR-AL52 Nylon Fabric reinforced
Seats, Diaphragm washers	Brass	Brass	Brass
Plug, Plug washer	Acetal Copolymer Black	Acetal Copolymer Black	Acetal Copolymer Black
Stopper Disk	PVC-U	n/a	n/a
Seal, O-Rings	NBR	NBR	NBR
Spring	Stainless steel 302	n/a	n/a
Shaft	Stainless steel 303	Stainless steel 303	Stainless steel 303
External Bolts, Nuts and Disks	Stainless steel	Stainless steel	Stainless steel
Chambers	Dual	Single	Single

Dimensions and Weights			
H (mm)	205	225	277
R (mm)	75	103	123
La (mm)	75	120	152
Lb (mm)	75	92	125
ØC (mm)	126	181	245
Weight (kg)	3.7	10.0	21.0