Toro Red Bottle

Toro Australia

Chemwatch Hazard Alert Code: 4

Chemwatch: **5230-86**
Version No: **4.1**
Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Initial Date: **02/12/2016**
Revision Date: **23/12/2022**
Print Date: **11/02/2026**
S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Toro Red Bottle
Chemical Name	Not Applicable
Synonyms	Part number: 112-0178, Product Code 04324 042320 .6B
Proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound); PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.

Details of the manufacturer or importer of the safety data sheet

Registered company name	**Toro Australia**
Address	53 Howards Road, Beverley South Australia 5009 Australia
Telephone	08 8300 3633
Fax	08 8243 2940
Website	www.toro.com.au
Email	info@toro.com.au

Emergency telephone number

Association / Organisation	**State EPA**	**CHEMWATCH EMERGENCY RESPONSE (24/7)**
Emergency telephone number(s)	000	+61 1800 951 288 (ID#: 5230-86)
Other emergency telephone number(s)	131 126	+61 3 9573 3188

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	S5
Classification [1]	Flammable Liquids Category 1, Aspiration Hazard Category 1, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Hazardous to the Aquatic Environment Acute Hazard Category 3
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI***

Label elements

Hazard pictogram(s)	
Signal word	**Danger**

Hazard statement(s)

H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.

Page 1 continued...

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
108-65-6	20-<30	propylene glycol monomethyl ether acetate, alpha-isomer
1330-20-7	20-<30	xylene
100-41-4	5-<10	ethylbenzene
96-29-7	0.1-<1	methyl ethyl ketoxime
13463-67-7	0.1-<1	titanium dioxide
108-88-3	0.1-<1	toluene
Not Available	40-<50	Ingredients determined not to be hazardous
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available***	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▸ Wash out immediately with fresh running water. ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▸ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▸ Immediately remove all contaminated clothing, including footwear. ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation.
Inhalation	▸ If fumes or combustion products are inhaled remove from contaminated area. ▸ Lay patient down. Keep warm and rested. ▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▸ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▸ Transport to hospital, or doctor.
Ingestion	▸ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. ▸ If swallowed do **NOT** induce vomiting. ▸ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▸ Observe the patient carefully. ▸ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▸ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▸ Seek medical advice. ▸ Avoid giving milk or oils. ▸ Avoid giving alcohol.

Continued...

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Do not use a water jet to fight fire.

Special hazards arising from the substrate or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ Wear breathing apparatus plus protective gloves in the event of a fire. ‣ Prevent, by any means available, spillage from entering drains or water courses. ‣ Use fire fighting procedures suitable for surrounding area. ‣ **DO NOT** approach containers suspected to be hot. ‣ Cool fire exposed containers with water spray from a protected location.
Fire/Explosion Hazard	‣ Liquid and vapour are highly flammable. ‣ Severe fire hazard when exposed to heat, flame and/or oxidisers. ‣ Vapour forms an explosive mixture with air. ‣ Severe explosion hazard, in the form of vapour, when exposed to flame or spark. ‣ Vapour may travel a considerable distance to source of ignition. ‣ Heating may cause expansion / decomposition with violent rupture of containers. Combustion products include: ‣ carbon dioxide (CO_2) ‣ other pyrolysis products typical of burning organic material.
HAZCHEM	●3YE

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	‣ Remove all ignition sources. ‣ Clean up all spills immediately. ‣ Avoid breathing vapours and contact with skin and eyes. ‣ Control personal contact with the substance, by using protective equipment. ‣ Contain and absorb small quantities with vermiculite or other absorbent material. ‣ Wipe up.
Major Spills	‣ Clear area of personnel and move upwind. ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ Wear breathing apparatus plus protective gloves. ‣ Prevent, by any means available, spillage from entering drains or water course. ‣ Stop leak if safe to do so. ‣ Contain spill with sand, earth or vermiculite.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	‣ Containers, even those that have been emptied, may contain explosive vapours. ‣ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. ‣ **DO NOT** allow clothing wet with material to stay in contact with skin The tendency of many ethers to form explosive peroxides is well documented. Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe ‣ **DO NOT** concentrate by evaporation, or evaporate extracts to dryness, as residues may contain explosive peroxides with DETONATION potential. ‣ Any static discharge is also a source of hazard. ‣ Before any distillation process remove trace peroxides by shaking with excess 5% aqueous ferrous sulfate solution or by percolation through a column of activated alumina. ‣ Distillation results in uninhibited ether distillate with considerably increased hazard because of risk of peroxide formation on storage. ‣ Add inhibitor to any distillate as required. The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example. Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised. ‣ A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation. An expiration date should be determined. The chemical should either be treated to remove peroxides or disposed of before this date. · Electrostatic discharge may be generated during pumping - this may result in fire. · Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Continued...

	· Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec). · Avoid splash filling. · Do NOT use compressed air for filling discharging or handling operations. · Wait 2 minutes after tank filling (for tanks such as those on · road tanker vehicles) before opening hatches or manholes. ▸ Avoid skin contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Prevent concentration in hollows and sumps. ▸ **DO NOT** enter confined spaces until atmosphere has been checked. ▸ Avoid smoking, naked lights, heat or ignition sources.
Other information	▸ Store in original containers in approved flame-proof area. ▸ No smoking, naked lights, heat or ignition sources. ▸ **DO NOT** store in pits, depression, basement or areas where vapours may be trapped. ▸ Keep containers securely sealed. ▸ Store away from incompatible materials in a cool, dry well ventilated area. ▸ Protect containers against physical damage and check regularly for leaks.

Conditions for safe storage, including any incompatibilities

Suitable container	▸ Packing as supplied by manufacturer. ▸ Plastic containers may only be used if approved for flammable liquid. ▸ Check that containers are clearly labelled and free from leaks. ▸ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. ▸ For materials with a viscosity of at least 2680 cSt. (23 deg. C) ▸ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C) ▸ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used. ▸ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages ▸ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	▸ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. ▸ Avoid reaction with oxidising agents Avoid contact with halogens

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	propylene glycol monomethyl ether acetate, alpha-isomer	1-Methoxy-2-propanol acetate	50 ppm / 274 mg/m3	548 mg/m3 / 100 ppm	Not Available	Not Available
Australia Exposure Standards	xylene	Xylene (o-, m-, p-isomers)	80 ppm / 350 mg/m3	655 mg/m3 / 150 ppm	Not Available	Not Available
Australia Exposure Standards	ethylbenzene	Ethyl benzene	100 ppm / 434 mg/m3	543 mg/m3 / 125 ppm	Not Available	Not Available
Australia Exposure Standards	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Australia Exposure Standards	toluene	Toluene	50 ppm / 191 mg/m3	574 mg/m3 / 150 ppm	Not Available	Not Available

Exposure controls

Appropriate engineering controls	**CARE:** Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Individual protection measures, such as personal protective equipment	
Eye and face protection	▸ Safety glasses with side shields. ▸ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] ▸ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.
Skin protection	See Hand protection below
Hands/feet protection	▸ Wear chemical protective gloves, e.g. PVC.

Continued...

	▸ Wear safety footwear or safety gumboots, e.g. Rubber For esters: ▸ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.
Body protection	See Other protection below
Other protection	▸ Overalls. ▸ PVC Apron. ▸ PVC protective suit may be required if exposure severe. ▸ Eyewash unit. ▸ Ensure there is ready access to a safety shower. ▸ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. ▸ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). ▸ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:
"Forsberg Clothing Performance Index".
The effect(s) of the following substance(s) are taken into account in the ***computer-generated*** selection:
Toro Red Bottle

Material	CPI
VITON	A
TEFLON	B
BUTYL	C
BUTYL/NEOPRENE	C
CPE	C
HYPALON	C
NAT+NEOPR+NITRILE	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
VITON/CHLOROBUTYL	C
VITON/NEOPRENE	C

* CPI - Chemwatch Performance Index
A: Best Selection
B: Satisfactory; may degrade after 4 hours continuous immersion
C: Poor to Dangerous Choice for other than short term immersion
NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -
* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Ansell Glove Selection

Glove — *In order of recommendation*
AlphaTec® 38-612
AlphaTec® 58-530B
AlphaTec® 58-530W
AlphaTec® Solvex® 37-185
AlphaTec® 58-008
AlphaTec® Solvex® 37-675
AlphaTec® 79-700
AlphaTec® 58-735

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Continued...

AlphaTec® 53-001
AlphaTec® 58-005

The suggested gloves for use should be confirmed with the glove supplier.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Flammable liquid.

Physical state	Liquid	**Relative density (Water = 1)**	1.02
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	432.22
pH (as supplied)	Not Applicable	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	-94.9	**Viscosity (cSt)**	Not Available
Initial boiling point and boiling range (°C)	136-1	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	12.8	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	HIGHLY FLAMMABLE.	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	6.8	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	1.2	**Volatile Component (%vol)**	55.87
Vapour pressure (kPa)	0.867	**Gas group**	Not Available
Solubility in water	Not Available	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**VOC g/L**	570.505134
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▸ Unstable in the presence of incompatible materials. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	There is sufficient evidence to classify this material as an aspiration hazard

Inhaled	Inhalation hazard is increased at higher temperatures. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.
Ingestion	The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.

Continued...

Skin Contact	Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

Toro Red Bottle	**TOXICITY**	**IRRITATION**
	Not Available	Not Available

propylene glycol monomethyl ether acetate, alpha-isomer	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: >2000 mg/kg[1]	Eye: no adverse effect observed (not irritating)[1]
	Oral (Rat) LD50: 3739 mg/kg[2]	Skin: no adverse effect observed (not irritating)[1]

xylene	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >1700 mg/kg[2]	Eye (Human): 200ppm
	Inhalation (Rat) LC50: 5000 ppm4h[2]	Eye (Rodent - rabbit): 5mg/24H - Severe
	Oral (Mouse) LD50; 2119 mg/kg[2]	Eye (Rodent - rabbit): 87mg - Mild
		Eye: adverse effect observed (irritating)[1]
		Skin (Rodent - rabbit): 100% - Moderate
		Skin (Rodent - rabbit): 500mg/24H - Moderate
		Skin (Rodent - rat): 60uL/8H - Mild
		Skin: adverse effect observed (irritating)[1]

ethylbenzene	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: 17800 mg/kg[2]	Eye (Rodent - rabbit): 500mg - Severe
	Inhalation (Rat) LC50: 17.2 mg/l4h[2]	Skin (Rodent - rabbit): 15mg/24H - Mild
	Oral (Rat) LD50: 3500 mg/kg[2]	

methyl ethyl ketoxime	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >184<1840 mg/kg[1]	Eye (Rodent - rabbit): 100uL - Severe
	Inhalation (Rat) LC50: >4.83 mg/l4h[1]	Eye: adverse effect observed (irreversible damage)[1]
	Oral (Rat) LD50: >900 mg/kg[1]	Skin: adverse effect observed (irritating)[1]

titanium dioxide	**TOXICITY**	**IRRITATION**
	dermal (hamster) LD50: >=10000 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
	Inhalation (Rat) LC50: >2.28 mg/l4h[1]	Skin (Human): 300ug/3D (intermittent) - Mild
	Oral (Rat) LD50: >=2000 mg/kg[1]	Skin: no adverse effect observed (not irritating)[1]

toluene	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: 12124 mg/kg[2]	Eye (Human): 300ppm
	Inhalation (Rat) LC50: >13350 ppm4h[2]	Eye (Rodent - rabbit): 0.1mL
	Oral (Rat) LD50: 636 mg/kg[2]	Eye (Rodent - rabbit): 0.1mL - Severe
		Eye (Rodent - rabbit): 100mg/30S - Mild
		Eye (Rodent - rabbit): 2mg/24H - Severe
		Eye (Rodent - rabbit): 870ug - Mild
		Eye: adverse effect observed (irritating)[1]
		Skin (Mammal - pig): 250uL/24H - Mild
		Skin (Rodent - rabbit): 20mg/24H - Moderate
		Skin (Rodent - rabbit): 435mg - Mild
		Skin (Rodent - rabbit): 500mg - Moderate
		Skin: adverse effect observed (irritating)[1]
		Skin: no adverse effect observed (not irritating)[1]

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

Continued...

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER	A BASF report (in ECETOC) showed that inhalation exposure to 545 ppm PGMEA (beta isomer) was associated with a teratogenic response in rabbits; but exposure to 145 ppm and 36 ppm had no adverse effects. The beta isomer of PGMEA comprises only 10% of the commercial material, the remaining 90% is alpha isomer. Hazard appears low but emphasizes the need for care in handling this chemical. [I.C.I] *Shin-Etsu SDS For propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA) and tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on the reproductive organs, the developing embryo and foetus, blood or thymus gland, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces and alkoxyacetic acid. The reproductive and developmental toxicities of the lower molecular weight homologues in the ethylene series are due specifically to the formation of methoxyacetic and ethoxyacetic acids. Longer chain homologues in the ethylene series are not associated with reproductive toxicity, but can cause haemolysis in sensitive species, also through formation of an alkoxyacetic acid. The predominant alpha isomer of all the PGEs (which is thermodynamically favoured during manufacture of PGEs) is a secondary alcohol incapable of forming an alkoxypropionic acid. In contrast, beta-isomers are able to form the alkoxypropionic acids and these are linked to birth defects (and possibly, haemolytic effects). Generally,linear and branched-chain alkyl esters are hydrolysed to their component alcohols and carboxylic acids in the intestinal tract, blood and most tissues throughout the body. Following hydrolysis the component alcohols and carboxylic acids are metabolized Oral acute toxicity studies have been reported for 51 of the 67 esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids. The very low oral acute toxicity of this group of esters is demonstrated by oral LD50 values greater than 1850 mg/kg bw Genotoxicity studies have been performed in vitro using the following esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids: methyl acetate, butyl acetate, butyl stearate and the structurally related isoamyl formate and demonstrates that these substances are not genotoxic. The JEFCA Committee concluded that the substances in this group would not present safety concerns at the current levels of intake the esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids are generally used as flavouring substances up to average maximum levels of 200 mg/kg. Higher levels of use (up to 3000 mg/kg) are permitted in food categories such as chewing gum and hard candy. In Europe the upper use levels for these flavouring substances are generally 1 to 30 mg/kg foods and in special food categories like candy and alcoholic beverages up to 300 mg/kg foods **Internationl Program on Chemical Safety: the Joint FAO/WHO Expert Committee on Food Additives (JECFA)** **Esters of Aliphatic acyclic primary alcohols with aliphatic linear saturated carboxylic acids.; 1998**
XYLENE	Reproductive effector in rats The substance is classified by IARC as Group 3: **NOT** classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
ETHYLBENZENE	Liver changes, utheral tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded. Ethylbenzene is readily absorbed when inhaled, swallowed or in contact with the skin. It is distributed throughout the body, and passed out through urine. It may irritate the skin, eyes and may cause hearing loss if exposed to high doses. Long Term exposure may cause damage to the kidney, liver and lungs, including a tendency to cancer formation, according to animal testing. There is no research on its effect on sex organs and unborn babies. **NOTE:** Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.
METHYL ETHYL KETOXIME	Mammalian lymphocyte mutagen *Huls Canada ** Merck The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. For methyl ethyl ketoxime (MEKO): At medium to high concentrations, MEKO increased the rate of liver tumours in animal testing. This seems to be due to the breakdown of MEKO into a cancer-causing substance, and occurred more often in males. MEKO does not seem to cause mutations. Repeated exposure appeared to cause effects on the nose, spleen, liver, kidney and blood. Animal testing suggests that MEKO did not cause reproductive or developmental effects below 10mg/kg body weight/day.
TITANIUM DIOXIDE	* IUCLID Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. Absorption by the stomach and intestines depends on the size of the particle. It penetrated only the outermost layer of the skin, suggesting that healthy skin may be an effective barrier. There is no substantive data on genetic damage, though cases have been reported in experimental animals. Studies have differing conclusions on its cancer-causing potential. No significant acute toxicological data identified in literature search. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
TOLUENE	For toluene: Acute toxicity: Humans exposed to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis (sleepiness) and death. When inhaled or swallowed, toluene can cause severe central nervous system depression, and in large doses has a narcotic effect. 60mL has caused death. Death of heart muscle fibres, liver swelling, congestion and bleeding of the lungs and kidney injury were all found on autopsy. Exposure to inhalation at a concentration of 600 parts per million for 8 hours resulted in the same and more serious symptoms including euphoria (a feeling of well-being), dilated pupils, convulsions and nausea. Exposure to 10000-30000 parts per million (1-3%) has been reported to cause narcosis and death. Toluene can also strip the skin of lipids, causing skin inflammation. Subchronic/chronic effects: Repeat doses of toluene cause adverse central nervous system effects and can damage the upper airway, the liver and the kidney.
XYLENE & ETHYLBENZENE	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
XYLENE & ETHYLBENZENE & TITANIUM DIOXIDE & TOLUENE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Continued...

ETHYLBENZENE & TITANIUM DIOXIDE	**WARNING:** This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✓	**Reproductivity**	✗
Serious Eye Damage/Irritation	✓	**STOT - Single Exposure**	✓
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✓

Legend: ✗ ***– Data either not available or does not fill the criteria for classification***
✓ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

Toro Red Bottle

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

propylene glycol monomethyl ether acetate, alpha-isomer

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	96h	Algae or other aquatic plants	>1000mg/l	2
LC50	96h	Fish	100-180mg/l	2
EC50	72h	Algae or other aquatic plants	>1000mg/l	2
EC50	48h	Crustacea	373mg/l	2
NOEC(ECx)	336h	Fish	47.5mg/l	2

xylene

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	4.6mg/l	2
EC50	48h	Crustacea	1.8mg/l	2
NOEC(ECx)	73h	Algae or other aquatic plants	0.44mg/l	2
LC50	96h	Fish	2.6mg/l	2

ethylbenzene

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	2.4-9.8mg/L	4
EC50	48h	Crustacea	1.37-4.4mg/l	4
EC50(ECx)	24h	Algae or other aquatic plants	0.02-938mg/L	4
EC50	96h	Algae or other aquatic plants	1.7-7.6mg/L	4
LC50	96h	Fish	3.381-4.075mg/L	4

methyl ethyl ketoxime

Endpoint	Test Duration (hr)	Species	Value	Source
BCF	1008h	Fish	0.5-0.6	7
EC50	72h	Algae or other aquatic plants	~6.09mg/l	2
EC50	48h	Crustacea	~201mg/l	2
NOEC(ECx)	72h	Algae or other aquatic plants	~1.02mg/l	2
LC50	96h	Fish	>100mg/l	2

titanium dioxide

Endpoint	Test Duration (hr)	Species	Value	Source
BCF	1008h	Fish	<1.1-9.6	7
EC50	72h	Algae or other aquatic plants	3.75-7.58mg/l	4
EC50	48h	Crustacea	1.9mg/l	2
NOEC(ECx)	672h	Fish	>=0.004mg/L	2
EC50	96h	Algae or other aquatic plants	179.05mg/l	2
LC50	96h	Fish	1.85-3.06mg/l	4

toluene

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	12.5mg/L	4
EC50	48h	Crustacea	3.78mg/L	5
NOEC(ECx)	168h	Crustacea	0.74mg/l	2
EC50	96h	Algae or other aquatic plants	>376.71mg/L	4
LC50	96h	Fish	5-35mg/l	4

Continued...

Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data***

Harmful to aquatic organisms.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol monomethyl ether acetate, alpha-isomer	LOW	LOW
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
methyl ethyl ketoxime	LOW	LOW
titanium dioxide	HIGH	HIGH
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
propylene glycol monomethyl ether acetate, alpha-isomer	LOW (LogKOW = 0.56)
xylene	MEDIUM (BCF = 740)
ethylbenzene	LOW (BCF = 79.43)
methyl ethyl ketoxime	LOW (BCF = 5.8)
titanium dioxide	LOW (BCF = 10)
toluene	LOW (BCF = 90)

Mobility in soil

Ingredient	Mobility
propylene glycol monomethyl ether acetate, alpha-isomer	HIGH (Log KOC = 1.838)
ethylbenzene	LOW (Log KOC = 517.8)
methyl ethyl ketoxime	LOW (Log KOC = 130.8)
titanium dioxide	LOW (Log KOC = 23.74)
toluene	LOW (Log KOC = 268)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	▸ Containers may still present a chemical hazard/ danger when empty. ▸ Return to supplier for reuse/ recycling if possible. Otherwise: ▸ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▸ Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: ▸ Reduction ▸ Reuse ▸ Recycling ▸ Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. ▸ **DO NOT** allow wash water from cleaning or process equipment to enter drains. ▸ It may be necessary to collect all wash water for treatment before disposal. ▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▸ Where in doubt contact the responsible authority. ▸ Recycle wherever possible. ▸ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. ▸ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). ▸ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 Transport information

Labels Required

Continued...

Marine Pollutant	NO
HAZCHEM	●3YE

Land transport (ADG)

14.1. **UN number or ID number**	1263
14.2. **UN proper shipping name**	PAINT RELATED MATERIAL (including paint thinning and reducing compound); PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
14.3. **Transport hazard class(es)**	Class: 3 Subsidiary Hazard: Not Applicable
14.4. **Packing group**	I
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: 163 367; 163 223 367 Limited quantity: 5 L

Air transport (ICAO-IATA / DGR)

14.1. **UN number**	1263
14.2. **UN proper shipping name**	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); PAINT RELATED MATERIAL (including paint thinning and reducing compound)
14.3. **Transport hazard class(es)**	ICAO/IATA Class: 3 ICAO / IATA Subsidiary Hazard: Not Applicable ERG Code: 3L
14.4. **Packing group**	I
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: A3 A72 A192 Cargo Only Packing Instructions: 361; 366 Cargo Only Maximum Qty / Pack: 30 L; 220 L Passenger and Cargo Packing Instructions: 351; 355 Passenger and Cargo Maximum Qty / Pack: 1 L; 60 L Passenger and Cargo Limited Quantity Packing Instructions: Forbidden; Y344 Passenger and Cargo Limited Maximum Qty / Pack: Forbidden; 10 L

Sea transport (IMDG-Code / GGVSee)

14.1. **UN number**	1263
14.2. **UN proper shipping name**	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); PAINT RELATED MATERIAL (including paint thinning and reducing compound)
14.3. **Transport hazard class(es)**	IMDG Class: 3 IMDG Subsidiary Hazard: Not Applicable
14.4. **Packing group**	I
14.5 **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	EMS Number: F-E, S-E Special provisions: 163 367; 163 223 367 955 Limited Quantities: 5 L

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
propylene glycol monomethyl ether acetate, alpha-isomer	Not Applicable
xylene	Not Applicable
ethylbenzene	Not Applicable
methyl ethyl ketoxime	Not Applicable
titanium dioxide	Not Applicable
toluene	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Continued...

Product name	Ship Type
propylene glycol monomethyl ether acetate, alpha-isomer	Not Applicable
xylene	Not Applicable
ethylbenzene	Not Applicable
methyl ethyl ketoxime	Not Applicable
titanium dioxide	Not Applicable
toluene	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

propylene glycol monomethyl ether acetate, alpha-isomer is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australian Inventory of Industrial Chemicals (AIIC)

xylene is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australian Inventory of Industrial Chemicals (AIIC)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

ethylbenzene is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australian Inventory of Industrial Chemicals (AIIC)
Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

methyl ethyl ketoxime is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australian Inventory of Industrial Chemicals (AIIC)
Chemical Footprint Project - Chemicals of High Concern List

titanium dioxide is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)
Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

toluene is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australian Inventory of Industrial Chemicals (AIIC)
Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (propylene glycol monomethyl ether acetate, alpha-isomer; xylene; ethylbenzene; methyl ethyl ketoxime; toluene)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes

Continued...

National Inventory	Status
UAE - Control List (Banned/Restricted Substances)	No (propylene glycol monomethyl ether acetate, alpha-isomer; xylene; ethylbenzene; methyl ethyl ketoxime; titanium dioxide; toluene)
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	23/12/2022
Initial Date	02/12/2016

SDS Version Summary

Version	Date of Update	Sections Updated
3.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
4.1	23/12/2022	Classification review due to GHS Revision change.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.
Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.